



**Description:** SILVYN UI 511\_  
**Lapp code:** Lapp 61799822

The **Test voltage** of the cable Lapp 61799822 is /.

## Application range

- Offshore applications
- Measuring technology
- Plant engineering
- Steel industry
- Applications with the highest mechanical stresses

## Product Make-up

- Spirally-wound stainless steel protective conduit with interlocked profile (AGRAFF)

In our Cable list on next page you can find all interesting information acc. article Lapp 61799822 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Static/dynamic bending radius in mm	Outer Ø (mm)	min. internal Ø	Internal Ø	PU (m)
SILVYN® UI 511							
SILVYN UI 511	Lapp 61799815	5/16"	50/60	12,5	9.5	9.5	30.0
SILVYN UI 511	Lapp 61799816	3/8"	65/80	16,5	13.0	13.0	30.0
SILVYN UI 511	Lapp 61799817	1/2"	75/100	20,3	17.0	17.0	30.0
SILVYN UI 511	Lapp 61799818	3/4"	90/125	25,3	22.0	22.0	30.0
SILVYN UI 511	Lapp 61799819	1."	120/160	31.0	25.8	25.8	30.0
SILVYN UI 511	Lapp 61799820	1 1/4"	175/220	39,5	34.2	34.2	30.0
SILVYN UI 511	Lapp 61799822	2."	285/340	58.0	52.0	52.0	15.0