



Description: SILVYN US 9_
Lapp code: Lapp 61795090

The **Test voltage** of the cable Lapp 61795090 is /.

Application range

- In combination with protective conduit
- SILVYN® FPS/FD-PU
- SILVYN® AS/EDU-AS/EMC AS-CU/AS-P
- Mechanical engineering
- Plant engineering

Product Make-up

- PG connection thread
- Hexagonal collar
- Inner sleeve (not included)
- Sealing element
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 61795090 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	PG size	Overall length/ C (mm)	D (mm)	F mm	SW 1/2 mm	Suitable for SILVYN® FPS/FD-PU	Suitable for SILVYN® AS	Suitable for SILVYN® E DU-AS/AS-P/EMC AS-CU	Pieces / PU
SILVYN® US										
SILVYN US 7	Lapp 61795080	7	28.0	7.0	9.5	15 / 17	7 x 10	8 x 10	7 x 10	50.0
SILVYN US 9	Lapp 61795090	9	30.0	7.0	11.5	19 / 21	10 x 14	11 x 14	10 x 14	50.0
SILVYN US 11	Lapp 61795100	11	30.0	7.0	15.5	23 / 25	13 x 17	14 x 17	13 x 17	50.0
SILVYN US 13.5	Lapp 61795110	13.5	30.0	7.0	17	25 / 27	15 x 19	16 x 19	15 x 19	50.0
SILVYN US 16	Lapp 61795120	16	30.0	7.0	19	27 / 29	16 x 21	18 x 21	17 x 21	50.0
SILVYN US 21	Lapp 61795130	21	40.0	10.0	24	34 / 36	22 x 27	23 x 27	22 x 27	25.0
SILVYN US 29	Lapp 61795140	29	40.0	10.0	32.5	43 / 45	29 x 36	31 x 36	29 x 36	25.0
SILVYN US 36	Lapp 61795150	36	40.0	10.0	42	52 / 54	38 x 45	40 x 45	38 x 45	20.0
SILVYN US 48	Lapp 61795170	48	45.0	10.0	55	63 / 77	48 x 56	51 x 56	49 x 56	10.0