



Description: SILVYN US-M 10 x 1.0_

Lapp code: Lapp 55501500

The **Test voltage** of the cable Lapp 55501500 is /.

Application range

- In combination with protective conduit
- SILVYN® FPS/FD-PU
- SILVYN®AS/EDU-AS/EMC AS-CU/AS-P
- Mechanical engineering
- Plant engineering

Product Make-up

- Metric connection thread
- Hexagonal collar
- Inner sleeve (not included)
- Sealing element
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 55501500 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Size M	SW 1/2 mm	C mm	D (mm)	Suitable for SILVYN® FD-PU/FPS	Suitable for SILVYN® AS	Suitable for SILVYN® ED U-AS/AS-P/EMC AS-CU	Pieces / PU
SILVYN® US-M									
SILVYN US-M 10 x 1.0	Lapp 55501500	10 x 1.0	15 / 17	31	10	7 x 10	8 x 10	7 x 10	50
SILVYN US-M 12 x 1.5	Lapp 55501510	12 x 1.5	19 / 21	33	10	10 x 14	11 x 14	10 x 14	50
SILVYN US-M 16 x 1.5	Lapp 55501520	16 x 1.5	23 / 25	33	10	13 x 17	14 x 17	13 x 17	50
SILVYN US-M 20 x 1.5	Lapp 55501530	20 x 1.5	27 / 29	33	10	16 x 21	18 x 21	17 x 21	50
SILVYN US-M 25 x 1.5	Lapp 55501540	25 x 1.5	34 / 36	41	11	22 x 27	23 x 27	22 x 27	25
SILVYN US-M 32 x 1.5	Lapp 55501550	32 x 1.5	43 / 45	43	13	29 x 36	31 x 36	29 x 36	25
SILVYN US-M 40 x 1.5	Lapp 55501560	40 x 1.5	52 / 54	43	13	38 x 45	40 x 45	38 x 44	20
SILVYN US-M 50 x 1.5	Lapp 55501570	50 x 1.5	63 / 66	49	14	48 x 56	51 x 56	49 x 56	10