



**Description:** SILVYN USK 29\_  
**Lapp code:** Lapp 52005870

The **Test voltage** of the cable Lapp 52005870 is /.

## Application range

- In combination with protective conduit
- SILVYN® FPS/ FD-PU
- SILVYN® SP/SP-PU
- Indoor applications
- Light mechanical stress

## Product Make-up

- PG connection thread
- Hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 52005870 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	PG size	Clear opening (mm)	Overall length/ C (mm)	Thread length/ D (mm)	SW 1/2 mm	Suitable for SILVYN® FD-PU/FPS	Suitable for SILVYN® SP/SP-PU	Pieces / PU
SILVYN® USK									
SILVYN USK 7	Lapp 52005810	7	6.0	40.0	10.0	18 / 16	7 x 10		50.0
SILVYN USK 9	Lapp 52005820	9	9.0	41.0	10.0	23 / 21	10 x 14	10 x 14	50.0
SILVYN USK 11	Lapp 52005830	11	11.0	41.0	10.0	27 / 24	13 x 17	12 x 16	50.0
SILVYN USK 13.5	Lapp 52005840	13.5	13.0	41.0	10.0	29 / 26	15 x 19	14 x 18	50.0
SILVYN USK 16	Lapp 52005850	16	14.5	42.0	11.0	32 / 29	16 x 21	16 x 20	50.0
SILVYN USK 21	Lapp 52005860	21	19.5	48.0	11.0	40 / 36	22 x 27	22 x 27	25.0
SILVYN USK 29	Lapp 52005870	29	27.0	48.0	12.0	49 / 45	29 x 36	30 x 36	25.0
SILVYN USK 36	Lapp 52005880	36	36.0	48.0	12.0	63 / 53	38 x 45	38 x 44	25.0
SILVYN USK 48	Lapp 52005900	48	46.0	57.0	15.0	70 / 65	48 x 56	50 x 56	10.0