



**Description:** SILVYN USK-M 12 x 1.5\_

**Lapp code:** Lapp 55501310

The **Test voltage** of the cable Lapp 55501310 is /.

## Application range

- In combination with protective conduit:
- SILVYN® FPS/ FD-PU
- SILVYN® SP/SP-PU
- Indoor applications
- Light mechanical stress

## Product Make-up

- Metric connection thread
- Hexagonal collar
- Threaded sleeve
- Cap nut

In our Cable list on next page you can find all interesting information acc. article Lapp 55501310 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Connection thread M	Clear opening (mm)	Overall length/ C (mm)	Thread length/ D (mm)	SW 1/2 mm	Suitable for SILVYN® FD-PU/FPS	Suitable for SILVYN® SP	Suitable for SILVYN® SP-PU	Pieces / PU
SILVYN® USK-M										
SILVYN USK-M 10 x 1.0	Lapp 55501300	10 x 1.0	6.0	40.0	10.0	18 / 16	7 x 10			50.0
SILVYN USK-M 12 x 1.5	Lapp 55501310	12 x 1.5	9.0	43.0	12.0	23 / 21	10 x 14	10 x 14	10 x 14	50.0
SILVYN USK-M 16 x 1.5	Lapp 55501320	16 x 1.5	13.0	43.0	12.0	27 / 24	13 x 17	12 x 16	12 x 16	50.0
SILVYN USK-M 20 x 1.5	Lapp 55501330	20 x 1.5	14.5	44.0	13.0	32 / 29	16 x 21	16 x 20	16 x 20	50.0
SILVYN USK-M 25 x 1.5	Lapp 55501340	25 x 1.5	19.5	50.0	13.0	40 / 36	22 x 27	22 x 27	22 x 27	25.0
SILVYN USK-M 32 x 1.5	Lapp 55501350	32 x 1.5	27.0	51.0	15.0	49 / 45	29 x 36	30 x 36	30 x 36	25.0
SILVYN USK-M 40 x 1.5	Lapp 55501360	40 x 1.5	36.0	51.0	15.0	58 / 53	38 x 45	38 x 44	38 x 44	25.0
SILVYN USK-M 50 x 1.5	Lapp 55501370	50 x 1.5	46.0	58.0	16.0	70 / 65	48 x 56	50 x 56		10.0