



Description: SKINDICHT SE_

Lapp code: Lapp 52004150

The **Test voltage** of the cable Lapp 52004150 is /.

Application range

- For high mechanical stress
- When no connection thread is provided

Product Make-up

- PG 16 - 21 with 2 screw holes
- PG 29 - 36 with 4 screw holes

In our Cable list on next page you can find all interesting information acc. article Lapp 52004150 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation / size	Incised sealing ring ØF (mm)	SW (mm)	Overall length (mm)	Overall width (mm)	Overall height (mm)	Pieces / PU
SKINDICHT® SE								
SKINDICHT SE	Lapp 52004130	SE 16	8/10.5/13.5/16	22	49,2	42	36.0	10
SKINDICHT SE	Lapp 52004140	SE 21	11/15/18/20	28	68,1	60	52,5	10
SKINDICHT SE	Lapp 52005430	SE 29	19/23/27/31	37	83,6	66	54.0	5
SKINDICHT SE	Lapp 52004150	SE 36	25/28/31/35	47	99,6	85	73.0	1
SKINDICHT® SE without E+D								
SKINDICHT SE	Lapp 52024090	SE 16			42.0	42	36.0	10
SKINDICHT SE	Lapp 52024100	SE 21			60.0	60	52,5	10
SKINDICHT SE	Lapp 52024110	SE 29			76.0	66	54.0	5
SKINDICHT SE	Lapp 52024120	SE 36			90.0	85	73.0	1