Description: **SKINDICHT SHV-M-VITON_**
Lapp code: Lapp 52105460

The **Test voltage** of the cable Lapp 52105460 is /.

Application range

- Watertight and high temperature-resistant cable gland with special conical VITON® sealing element.
- Brickworks
- Sewage treatment plants
- Car wash sites

Product Make-up

- 1 fitting
- 2 washers
- 3 VITON® sealing cone
- 4 brass cones
- 5 compression screws

In our Cable list on next page you can find all interesting information acc. article Lapp 52105460 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation / size	Clamping range ØF (mm)	Function thread PG	SW (mm)	Overall length/ C (mm)	Thread length/ D (mm)	Clear opening F (mm)	Pieces / PU
SKINDICHT® SHV-M-VITON®									
SKINDICHT SHV-M-VITON	Lapp 52105430	12 x 1,5	3,8 - 4,8	7	14 / 14	26.0	5.0	5	50
SKINDICHT SHV-M-VITON	Lapp 52105440	16 x 1,5	4,8 - 5,8	9	18 / 17	27,5	5.0	6	50
SKINDICHT SHV-M-VITON	Lapp 52105450	16 x 1,5	5,8 - 6,8	9	18 / 17	27,5	5.0	7	50
SKINDICHT SHV-M-VITON	Lapp 52105460	20 x 1,5	5,8 - 6,8	11	22 / 20	31.0	6.0	7	25
SKINDICHT SHV-M-VITON	Lapp 52105470	20 x 1,5	6,8 - 8,8	11	22 / 20	31.0	6.0	9	25
SKINDICHT SHV-M-VITON	Lapp 52105480	20 x 1,5	8,5 - 10,8	13.5	22 / 22	32,5	6.0	11	25
SKINDICHT SHV-M-VITON	Lapp 52105490	20 x 1,5	6,8 - 8,8	13.5	22 / 22	32,5	6.0	9	25
SKINDICHT SHV-M-VITON	Lapp 52105500	20 x 1,5	10,8 - 12,8	16	24 / 24	34,5	6.0	13	25
SKINDICHT SHV-M-VITON	Lapp 52105510	20 x 1,5	13,8 - 14,8	16	24 / 24	34,5	6.0	15	25
SKINDICHT SHV-M-VITON	Lapp 52105520	25 x 1,5	15,8 - 17,8	21	30 / 30	38.0	7.0	18	25
SKINDICHT SHV-M-VITON	Lapp 52105530	25 x 1,5	17,5 - 19,8	21	30 / 30	38.0	7.0	20	25
SKINDICHT SHV-M-VITON	Lapp 52105540	32 x 1,5	19,5 - 21,8	29	40 / 40	44,5	8.0	22	10

PERTRONIC CABLES SASA PERIC ROSENSTR.6 74239 HARDTHAUSEN TEL: 07139-507-8687 FAX: 07139-507-8680
www.pertronic-cables.com | sales@pertronic.eu | Skype PERTRONIC-CABLES | see you GOOGLE + PERTRONIC KABEL