



Description: SKINDICHT SR-SV-M_

Lapp code: Lapp 52105830

The **Test voltage** of the cable Lapp 52105830 is /.

Application range

- Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1
- Special cable gland with VITON® anti-kink sleeve. Our own reinforced acid-resistant VITON® receptacle does not show any effects of aging even after an extended period of use at a temperature of +165°C.
- Machine and turbine manufacturing
- Power plant engineering
- Laboratory

Product Make-up

- Metric connection thread acc. to EN 50262

In our Cable list on next page you can find all interesting information acc. article Lapp 52105830 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation / size	Clamping range ØF (mm)	Max. fitting size for installation (mm)	Function thread PG	SW1/SW2 mm	Overall length/ C (mm)	Thread length/ D (mm)	Clear opening F (mm)	Pieces / PU
SKINDICHT® SR-SV-M										
SKINDICHT SR-SV-M	Lapp 52105820	20 x 1,5	5,5 - 7	28	11	22 / 20	56.0	6.0	7	25
SKINDICHT SR-SV-M	Lapp 52105830	20 x 1,5	7,5 - 9	28	11	22 / 20	56.0	6.0	9	25
SKINDICHT SR-SV-M	Lapp 52105840	20 x 1,5	7,5 - 9	32	13.5	22 / 22	61,5	6.0	9	25
SKINDICHT SR-SV-M	Lapp 52105850	20 x 1,5	8,5 - 11	32	13.5	22 / 22	61,5	6.0	11	25
SKINDICHT SR-SV-M	Lapp 52105860	20 x 1,5	10,5 - 13	32	13.5	22 / 22	61,5	6.0	13	25
SKINDICHT SR-SV-M	Lapp 52105870	20 x 1,5	11 - 13	35	16	24 / 24	66,5	6.0	13	10
SKINDICHT SR-SV-M	Lapp 52105880	20 x 1,5	12 - 15	35	16	24 / 24	66,5	6.0	15	10
SKINDICHT SR-SV-M	Lapp 52105890	25 x 1,5	13,5 - 15	40	21	30 / 30	79.0	7.0	15	10
SKINDICHT SR-SV-M	Lapp 52105900	25 x 1,5	15,5 - 17	46	21	30 / 30	79.0	7.0	17	10
SKINDICHT SR-SV-M	Lapp 52105910	25 x 1,5	16,5 - 19	46	21	30 / 30	79.0	7.0	19	10