



Description: SKINTOP K-M ATEX plus_

Lapp code: Lapp 54115260

The **Test voltage** of the cable Lapp 54115260 is /.

Application range

- Devices, machines and apparatus of enhanced safety protection type "e"
- Equipment group II / Category 2G+1D
- For mobile applications in offshore and marine industries
- Chemical and petrochemical industry

Product Make-up

- Metric connection thread acc. to EN 50262

In our Cable list on next page you can find all interesting information acc. article Lapp 54115260 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation / size	Clamping range ØF (mm)	Thread M	SW (mm)	Overall length/ C (mm)	Thread length/ D (mm)	Pieces / PU
SKINTOP® K-M ATEX plus								
SKINTOP K-M ATEX plus	Lapp 54115200	K-M 12 ATEX plus	3-5,5	12 x 1.5	15	26,5 - 30	8.0	50
SKINTOP K-M ATEX plus	Lapp 54115210	K-M 16 ATEX plus	7-9	16 x 1.5	19	29 - 34	8.0	50
SKINTOP K-M ATEX plus	Lapp 54115220	K-M 20 ATEX plus	7-13	20 x 1.5	25	34 - 37	9.0	50
SKINTOP K-M ATEX plus	Lapp 54115230	K-M 25 ATEX plus	11-17	25 x 1.5	30	35 - 40	10.0	25
SKINTOP K-M ATEX plus	Lapp 54115240	K-M 32 ATEX plus	12-21	32 x 1.5	36	39 - 47	10.0	25
SKINTOP K-M ATEX plus	Lapp 54115250	K-M 40 ATEX plus	19-28	40 x 1.5	46	43 - 52	10.0	10
SKINTOP K-M ATEX plus	Lapp 54115260	K-M 50 ATEX plus	27-35	50 x 1.5	55	54 - 62	12.0	5
SKINTOP K-M ATEX plus	Lapp 54115270	K-M 63 ATEX plus	36-45	63 x 1.5	66	59 - 71	12.0	5