



**Description:** SKINTOP MS-M ATEX BRUSH\_

**Lapp code:** Lapp 52110024

The **Test voltage** of the cable Lapp 52110024 is /.

## Application range

- For EMC-compliant earthing of the copper braiding, or for cables with copper shaft sheath
- Chemical and petrochemical industry
- Plant engineering
- Equipment group II / Category 2G+1D
- Devices, machines and apparatus of enhanced safety protection type "e"

## Product Make-up

- Metric connection thread acc. to EN 50262

In our Cable list on next page you can find all interesting information acc. article Lapp 52110024 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation / size	Outer Ø (mm)/ from - to	Minimum Ø above braiding (mm)	SW (mm)	Thread length/ D (mm)	Pieces / PU
SKINDICHT® SHVE-M ATEX							
SKINTOP MS-M ATEX BRUSH	Lapp 52107102	20 x 1,5	6,9 - 8,9	5	22	6.0	10
SKINTOP® MS-M ATEX BRUSH							
SKINTOP MS-M ATEX BRUSH	Lapp 52110023	25 x 1,5	9 - 17	6	29	8.0	10
SKINTOP MS-M ATEX BRUSH	Lapp 52110024	32 x 1,5	11 - 21	8	36	9.0	1
SKINTOP MS-M ATEX BRUSH	Lapp 52110025	40 x 1,5	19 - 28	10	45	9.0	1
SKINTOP MS-M ATEX BRUSH	Lapp 52110026	50 x 1,5	27 - 35	14	54	10.0	1
SKINTOP MS-M ATEX BRUSH	Lapp 52110027	63 x 1,5	34 - 45	20	67	15.0	1
SKINTOP MS-M ATEX BRUSH	Lapp 52110028	63 x 1,5 plus	44 - 55	25	75	15.0	1