



Description: SKINTOP MS-M ATEX_

Lapp code: Lapp 53112720

The **Test voltage** of the cable Lapp 53112720 is /.

Application range

- Devices, machines and apparatus of enhanced safety protection type "e"
- Equipment group II / Category 2G+1D
- For mobile applications in offshore and marine industries
- Chemical and petrochemical industry

Product Make-up

- Metric connection thread acc. to EN 50262

In our Cable list on next page you can find all interesting information acc. article Lapp 53112720 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation / size	Clamping range ØF (mm)	SW (mm)	Overall length/ C (mm)	Thread length/ D (mm)	Pieces / PU
SKINTOP® MS-M ATEX							
SKINTOP MS-M ATEX	Lapp 53112700	12 x 1,5	3 - 7	16	26,5	6.5	100
SKINTOP MS-M ATEX	Lapp 53112710	16 x 1,5	4,5 - 10	20	33.0	7.0	100
SKINTOP MS-M ATEX	Lapp 53112720	20 x 1,5	7 - 13	24	37.0	8.0	50
SKINTOP MS-M ATEX	Lapp 53112730	25 x 1,5	9 - 17	29	38,5	8.0	25
SKINTOP MS-M ATEX	Lapp 53112740	32 x 1,5	11 - 21	36	45,5	9.0	25
SKINTOP MS-M ATEX	Lapp 53112750	40 x 1,5	19 - 28	45	48.0	9.0	10
SKINTOP MS-M ATEX	Lapp 53112760	50 x 1,5	26 - 35	54	55,5	10.0	5
SKINTOP MS-M ATEX	Lapp 53112770	63 x 1,5	34 - 45	67	67.0	15.0	5
SKINTOP MS-M ATEX	Lapp 53112779	63 x 1,5 plus	44 - 55	75	65,5	15.0	1
SKINTOP® MS-M-XL ATEX							
SKINTOP MS-M ATEX	Lapp 53112800	12 x 1,5	3 - 7	16	32,8	12.0	100
SKINTOP MS-M ATEX	Lapp 53112810	16 x 1,5	4,5 - 10	20	37.0	12.0	100
SKINTOP MS-M ATEX	Lapp 53112820	20 x 1,5	7 - 13	24	39,5	12.0	50
SKINTOP MS-M ATEX	Lapp 53112830	25 x 1,5	9 - 17	29	41,5	12.0	25
SKINTOP MS-M ATEX	Lapp 53112840	32 x 1,5	11 - 21	36	48,2	15.0	25
SKINTOP MS-M ATEX	Lapp 53112850	40 x 1,5	19 - 28	45	53,5	15.0	10
SKINTOP MS-M ATEX	Lapp 53112860	50 x 1,5	26 - 35	54	57,5	15.0	5