



Description: SKINTOP MS-SC-M_
Lapp code: Lapp 53112670

The **Test voltage** of the cable Lapp 53112670 is /.

Application range

- For EMC-compliant earthing of the copper braiding, or for cables with copper shaft sheath
- Telecommunication
- Industrial machinery and plant engineering
- Measurement and control technology
- Automation technology

Product Make-up

- Metric connection thread acc. to EN 50262

In our Cable list on next page you can find all interesting information acc. article Lapp 53112670 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation / size	Outer Ø (mm)/ from - to	Minimum Ø above braiding (mm)	SW (mm)	Thread length/ D (mm)	Pieces / PU
SKINTOP® MS-SC-M							
SKINTOP MS-SC-M	Lapp 53112610	12 x 1,5	3,5 - 7	2	16	6.5	50
SKINTOP MS-SC-M	Lapp 53112620	16 x 1,5	4,5 - 9	4	20	7.0	50
SKINTOP MS-SC-M	Lapp 53112630	20 x 1,5	7 - 12,5	5	24	8.0	25
SKINTOP MS-SC-M	Lapp 53112640	25 x 1,5	9 - 16,5	7.5	29	8.0	25
SKINTOP MS-SC-M	Lapp 53112650	32 x 1,5	11 - 21	9	36	9.0	25
SKINTOP MS-SC-M	Lapp 53112660	40 x 1,5	19 - 28	15	45	9.0	10
SKINTOP MS-SC-M	Lapp 53112670	50 x 1,5	27 - 35	21	54	10.0	5
SKINTOP® MS-SC-M-XL							
SKINTOP MS-SC-M	Lapp 53112625	16 x 1,5	4,5 - 9	4	20	12.0	50
SKINTOP MS-SC-M	Lapp 53112635	20 x 1,5	7 - 12,5	5	24	12.0	25
SKINTOP MS-SC-M	Lapp 53112645	25 x 1,5	9 - 16,5	7.5	29	12.0	25
SKINTOP MS-SC-M	Lapp 53112655	32 x 1,5	11 - 21	9	36	15.0	25
SKINTOP MS-SC-M	Lapp 53112665	40 x 1,5	19 - 28	15	45	15.0	10
SKINTOP MS-SC-M	Lapp 53112675	50 x 1,5	27 - 35	21	54	15.0	5