



**Description:** TBW - TBM shrink tube\_

**Lapp code:** Lapp 61810110

The **Test voltage** of the cable Lapp 61810110 is /.

## Application range

- Thick and medium-wall shrink tubes for 600 V, 90°C low voltage applications in continuous use
- Ideal for the protection of cable joints and terminations in low voltage power applications

/

In our Cable list on next page you can find all interesting information acc. article Lapp 61810110 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article description	Internal Ø before contraction (mm)	Shrinkage range (mm)	Panel thickness/ shrunk +- 0.1 mm	Pieces / PU
TBW / TBM shrink tube	Lapp 61810080	TBW 0350	8.9	3.0	1.8	5.0
TBW / TBM shrink tube	Lapp 61810090	TBW 0750	19.1	6,1	2.4	5.0
TBW / TBM shrink tube	Lapp 61810100	TBW 1500	38.1	11,9	4.1	2.0
TBW / TBM shrink tube	Lapp 61810110	TBW 2000	50.8	16.0	4.1	1.0
TBW / TBM shrink tube	Lapp 61810130	TBW 4700	119.9	39,9	4.3	1.0
TBW / TBM shrink tube	Lapp 61810140	TBM 0750	19.1	5,6	2	5.0
TBW / TBM shrink tube	Lapp 61810150	TBM 1100	27.9	10,2	2	3.0
TBW / TBM shrink tube	Lapp 61810160	TBM 1500	38.1	12,7	2	2.0
TBW / TBM shrink tube	Lapp 61810170	TBM 2050	52.1	19,1	2	1.0
TBW / TBM shrink tube	Lapp 61810180	TBM 3500	88.9	30.0	2.4	1.0
TBW / TBM shrink tube	Lapp 61810190	TBM 6700	170.2	58,4	2.8	1.0
TBW / TBM shrink tube	Lapp 61810200	TBM 9000	228.6	77.0	3	1.0