



Description: TY- RAP weather-proof, UV-stabilised_
Lapp code: Lapp 61723010

The **Test voltage** of the cable Lapp 61723010 is /.

Application range

- Used for outdoor installation and maintenance of power plants

/

In our Cable list on next page you can find all interesting information acc. article Lapp 61723010 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article description	UL approval	Length x width (mm)	Bundling Ø (mm)	Tensile strength (N)	Pieces / PU
TY-RAP® weather-resistant							
TY- RAP weather-proof, UV-stabilised	Lapp 61723010	TYB* 23 MX	no	92 x 2,4	2 - 16	80	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723110	TY 232 MX	no	200 x 2,4	2 - 50	80	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723120	TY 234 MX	no	356 x 2,4	2 - 102	80	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723020	TYB* 24 MX	no	140 x 3,6	2 - 29	180	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723130	TY 242 MX	yes	208 x 3,6	2 - 50	180	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723040	TY 26 MX	yes	281 x 3,6	2 - 76	180	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723140	TY 244 MX	no	368 x 3,6	2 - 103	180	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723030	TYB* 25 MX	no	186 x 4,8	3,5 - 45	220	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723150	TY 253 MX	no	293 x 4,8	3,5 - 78	220	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723060	TY 28 MX	yes	360 x 4,8	3,5 - 102	220	1000
TY- RAP weather-proof, UV-stabilised	Lapp 61723160	TY 272 MX	no	223 x 7,6	6 - 50	540	500
TY- RAP weather-proof, UV-stabilised	Lapp 61723050	TY 27 MX	yes	340 x 7	6 - 90	540	500
TY- RAP weather-proof, UV-stabilised	Lapp 61723070	TY 29 MX	no	762 x 7,6	6 - 229	540	500