

LAPP KABEL STUFGART UNITRONIC® BUS ASI FD

Description: UNITRONIC BUS ASI FD_

Lapp code: Lapp 2170318

The **Test voltage** of the cable Lapp 2170318 is Core/core: 2000 V.

Application range

- Communication at sensor/actuator level
- UNITRONIC® Fieldbus sensor-/actuator wiring

Product Make-up

- Extra-fine wire, tinned copper strands
- Core insulation: blue and brown
- Profiled outer sheath: TPE or PUR
- Colour: yellow (RAL 1023) or black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170318 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Outer sheath material	Outer sheath colour	Application	Number of cores and mm ² per conductor	Copper index (kg/km)	Weight (kg/km)
For highly flexible applications (power chains, moving machine parts)								
UNITRONIC BUS ASI FD	Lapp 2170357	UNITRONIC® BUS ASI FD P FRNC	PUR UL/CSA (AWM)	yellow	Data and power transmission	2 x 1,5	29.0	64
UNITRONIC BUS ASI FD	Lapp 2170358	UNITRONIC® BUS ASI FD P FRNC	PUR UL/CSA (AWM)	black	Transmission of 30 V DC auxiliary power	2 x 1,5	29.0	64
UNITRONIC BUS ASI FD	Lapp 2170317	UNITRONIC® BUS ASI LD FD P	PUR UL/CSA (AWM)	yellow	Data and power transmission	2 x 2,5	48.0	74
UNITRONIC BUS ASI FD	Lapp 2170318	UNITRONIC® BUS ASI LD FD P	PUR UL/CSA (AWM)	black	Transmission of 30 V DC auxiliary power	2 x 2,5	48.0	74
UNITRONIC BUS ASI FD	Lapp 2170830	UNITRONIC® BUS ASI FD (TPE) A	TPE UL/CSA (AWM)	yellow	Data and power transmission	2 x 1,5	29.0	64
UNITRONIC BUS ASI FD	Lapp 2170831	UNITRONIC® BUS ASI FD (TPE) A	TPE UL/CSA (AWM)	black	Transmission of 30 V DC auxiliary power	2 x 1,5	29.0	64