

LAPP KABEL STUFGART UNITRONIC® BUS ASI FD

Description: UNITRONIC BUS ASI FD_

Lapp code: Lapp 2170831

The **Test voltage** of the cable Lapp 2170831 is Core/core: 2000 V.

Application range

- Communication at sensor/actuator level
- UNITRONIC® Fieldbus sensor-/actuator wiring

Product Make-up

- Extra-fine wire, tinned copper strands
- Core insulation: blue and brown
- Profiled outer sheath: TPE or PUR
- Colour: yellow (RAL 1023) or black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170831 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | Outer sheath material | Outer sheath colour | Application | Number of cores and mm ² per conductor | Copper index (kg/km) | Weight (kg/km) |
|---|--------------|-------------------------------|-----------------------|---------------------|---|---|----------------------|----------------|
| For highly flexible applications (power chains, moving machine parts) | | | | | | | | |
| UNITRONIC BUS ASI FD | Lapp 2170357 | UNITRONIC® BUS ASI FD P FRNC | PUR UL/CSA (AWM) | yellow | Data and power transmission | 2 x 1,5 | 29.0 | 64 |
| UNITRONIC BUS ASI FD | Lapp 2170358 | UNITRONIC® BUS ASI FD P FRNC | PUR UL/CSA (AWM) | black | Transmission of 30 V DC auxiliary power | 2 x 1,5 | 29.0 | 64 |
| UNITRONIC BUS ASI FD | Lapp 2170317 | UNITRONIC® BUS ASI LD FD P | PUR UL/CSA (AWM) | yellow | Data and power transmission | 2 x 2,5 | 48.0 | 74 |
| UNITRONIC BUS ASI FD | Lapp 2170318 | UNITRONIC® BUS ASI LD FD P | PUR UL/CSA (AWM) | black | Transmission of 30 V DC auxiliary power | 2 x 2,5 | 48.0 | 74 |
| UNITRONIC BUS ASI FD | Lapp 2170830 | UNITRONIC® BUS ASI FD (TPE) A | TPE UL/CSA (AWM) | yellow | Data and power transmission | 2 x 1,5 | 29.0 | 64 |
| UNITRONIC BUS ASI FD | Lapp 2170831 | UNITRONIC® BUS ASI FD (TPE) A | TPE UL/CSA (AWM) | black | Transmission of 30 V DC auxiliary power | 2 x 1,5 | 29.0 | 64 |