

LAPP KABEL STUFLIANG UNITRONIC® BUS ASI

Description: UNITRONIC BUS ASI_
Lapp code: Lapp 2170228

The **Test voltage** of the cable Lapp 2170228 is Core/core: 2000 V.

Application range

- Communication at sensor/actuator level
- UNITRONIC® Fieldbus sensor-/actuator wiring
- For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load
- The TPE version has an oil-resistant outer sheath. It is suitable for wet areas, in particular in conjunction with water-soluble cooling lubricants.

Product Make-up

- Extra-fine wire, tinned copper strands
- Core insulation: blue and brown
- Profiled outer sheath made of rubber (G), thermoplastic elastomers (TPE) or PVC
- Colour: yellow (RAL 1023) or black (RAL 9005)
- Colour: red (RAL 3000)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170228 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Outer sheath material	Outer sheath colour	Application	Number of cores and mm ² per conductor	Copper index (kg/km)	Weight (kg/km)
For fixed and flexible applications (19-wire stranded conductor)								
UNITRONIC BUS ASI	Lapp 2170228	UNITRONIC® BUS ASI (G)	EPDM (rubber)	yellow	Data and power transmission	2 x 1,5	29.0	85
UNITRONIC BUS ASI	Lapp 2170229	UNITRONIC® BUS ASI (G)	EPDM (rubber)	black	Transmission of 30 V DC auxiliary power	2 x 1,5	29.0	85
UNITRONIC BUS ASI	Lapp 2170371	UNITRONIC® BUS ASI LD (G)	EPDM (rubber)	yellow	Data and power transmission	2 x 2,5	48.0	85
UNITRONIC BUS ASI	Lapp 2170372	UNITRONIC® BUS ASI LD (G)	EPDM (rubber)	black	Transmission of 30 V DC auxiliary power	2 x 2,5	48.0	85
UNITRONIC BUS ASI	Lapp 2170230	UNITRONIC® BUS ASI (TPE)	TPE	yellow	Data and power transmission	2 x 1,5	29.0	64
UNITRONIC BUS ASI	Lapp 2170231	UNITRONIC® BUS ASI (TPE)	TPE	black	Transmission of 30 V DC auxiliary power	2 x 1,5	29.0	64
UNITRONIC BUS ASI	Lapp 2170232	UNITRONIC® BUS ASI (TPE)	TPE	red	Transmission of 230 V AC auxiliary power	2 x 1,5	29.0	64
UNITRONIC BUS ASI	Lapp 2170842	UNITRONIC® BUS ASI (PVC) A	PVC UL/CSA (CMG)	yellow	Data and power transmission	2 x 1,5	29.0	70
UNITRONIC BUS ASI	Lapp 2170843	UNITRONIC® BUS ASI (PVC) A	PVC UL/CSA (CMG)	black	Transmission of 30 V DC auxiliary power	2 x 1,5	29.0	70
UNITRONIC BUS ASI	Lapp 2170844	UNITRONIC® BUS ASI (PVC) A	PVC UL/CSA (CMG)	red	Transmission of 230 V AC auxiliary power	2 x 1,5	29.0	70