



Description: UNITRONIC BUS CAN BURIAL 4 x 1 x 0,5_

Lapp code: Lapp 2170500

The **Test voltage** of the cable Lapp 2170500 is Core/core: 1500 V rms.

Application range

- Useable for CAN based communication systems like CANopen
- Suitable for direct burial
- For outdoor applications
- For fixed installation or applications with occasional movements

Product Make-up

- Copper stranded 7x0,32
- Core insulation made of polyethylene (PE)
- Colour-coded in accordance with DIN 47100
- Overall screening of braided tinned-copper strands
- Sheath 1: PVC violet, Outer diameter 7,1 mm
- Sheath 2: PE black, Outer diameter ca. 9 mm

In our Cable list on next page you can find all interesting information acc. article Lapp 2170500 and much more.

UNITRONIC BUS CAN BURIAL 4 x 1 x 0,5_

Lapp 2170500



CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of pairs/conductor cross section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC BUS CAN BURIAL 4 x 1 x 0,5	Lapp 2170500	4 x 1 x 0,5	9.0	41.8	91.0