



**Description:** UNITRONIC BUS CAN FD P\_

**Lapp code:** Lapp 2170279

The **Test voltage** of the cable Lapp 2170279 is Core/core: 1500 V rms.

## Application range

- For highly flexible applications

## Product Make-up

- Stranded bare conductor
- Screening: wrapped with braided copper wires
- PUR outer sheath
- Colour: violet (RAL 4001)
- UV-resistant (but colour may change after some time)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170279 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs/conductor cross section (mm <sup>2</sup> )	Outer diameter (mm)	Conductor resistance	Copper index (kg/km)	Weight (kg/km)
For highly flexible applications (power chains, moving machine parts)							
UNITRONIC BUS CAN FD P	Lapp 2170272	UNITRONIC® BUS CAN FD P	1 x 2 x 0,25	6.4	159.8	24.0	40.0
UNITRONIC BUS CAN FD P	Lapp 2170273	UNITRONIC® BUS CAN FD P	2 x 2 x 0,25	8.4	159.8	33.0	65.0
UNITRONIC BUS CAN FD P	Lapp 2170275	UNITRONIC® BUS CAN FD P	1 x 2 x 0,34	6.8	122.0	32.8	60.0
UNITRONIC BUS CAN FD P	Lapp 2170276	UNITRONIC® BUS CAN FD P	2 x 2 x 0,34	9.6	122.0	52.4	88.0
UNITRONIC BUS CAN FD P	Lapp 2170278	UNITRONIC® BUS CAN FD P	1 x 2 x 0,5	8.0	72.8	41.9	74.0
UNITRONIC BUS CAN FD P	Lapp 2170279	UNITRONIC® BUS CAN FD P	2 x 2 x 0,5	10.8	72.8	59.4	100.0