



**Description:** UNITRONIC BUS CAN\_

**Lapp code:** Lapp 2170263

The **Test voltage** of the cable Lapp 2170263 is Core/core: 1500 V rms.

## Application range

- Fixed installation

## Product Make-up

- 0.22 + 0.34 + 0.5: bare stranded conductor, 7-wire  
0.75: bare stranded conductor, fine-wire
- Colour-coded in accordance with DIN 47100
- Copper braid
- PVC sheath
- Colour: violet (RAL 4001)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170263 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs/conductor cross section (mm <sup>2</sup> )	Outer diameter (mm)	Conductor resistance	Copper index (kg/km)	Weight (kg/km)
for fixed installation							
UNITRONIC BUS CAN	Lapp 2170260	UNITRONIC® BUS CAN	1 x 2 x 0,22	5.7	186.0	16.7	42.0
UNITRONIC BUS CAN	Lapp 2170261	UNITRONIC® BUS CAN	2 x 2 x 0,22	7.6	186.0	34.8	68.0
UNITRONIC BUS CAN	Lapp 2170263	UNITRONIC® BUS CAN	1 x 2 x 0,34	6.8	115.0	25.0	55.0
UNITRONIC BUS CAN	Lapp 2170264	UNITRONIC® BUS CAN	2 x 2 x 0,34	8.5	115.0	46.4	88.0
UNITRONIC BUS CAN	Lapp 2170266	UNITRONIC® BUS CAN	1 x 2 x 0,5	7.5	78.0	41.6	90.0
UNITRONIC BUS CAN	Lapp 2170267	UNITRONIC® BUS CAN	2 x 2 x 0,5	9.6	78.0	59.4	106.0
UNITRONIC BUS CAN	Lapp 2170269	UNITRONIC® BUS CAN	1 x 2 x 0,75	8.7	52.0	52.7	108.0
UNITRONIC BUS CAN	Lapp 2170270	UNITRONIC® BUS CAN	2 x 2 x 0,75	11.5	52.0	80.6	142.0