



Description: UNITRONIC BUS FF_
Lapp code: Lapp 2170351

The **Test voltage** of the cable Lapp 2170351 is 1500 V.

Application range

- FOUNDATION™ Fieldbus is used in intrinsically safe areas, especially in the field of Process Automation
- Fixed installation

Product Make-up

- Lapp bus cables for FOUNDATION™ field bus are available in 4 versions:
- 3-core, unarmoured, with device ground
- 3-core, armoured (longitudinally welded, spiral corrugated copper sheath) with device ground
Yellow and blue version
- 2-core, not armoured, with device ground

In our Cable list on next page you can find all interesting information acc. article Lapp 2170351 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | Number of pairs and AWG per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------|--------------|------------------------------|---------------------------------------|---------------------|----------------------|----------------|
| UNITRONIC BUS FF | Lapp 2170350 | UNITRONIC® BUS FF 3 | 1x2x1.1 + 1x1.1 Ø | 7.9 | 62.0 | 93 |
| UNITRONIC BUS FF | Lapp 2170351 | UNITRONIC® BUS FF 3 ARM (YE) | 1x2x1.1 + 1x1.1 Ø | 12.3 | 125.0 | 182 |
| UNITRONIC BUS FF | Lapp 2170353 | UNITRONIC® BUS FF 3 ARM (BU) | 1x2x1.1 + 1x1.1 Ø | 12.3 | 125.0 | 182 |
| UNITRONIC BUS FF | Lapp 2170352 | UNITRONIC® BUS FF 2 | 1 x 2 x 1,1 | 7.9 | 53.3 | 82 |