



Description: UNITRONIC BUS FF_

Lapp code: Lapp 2170353

The **Test voltage** of the cable Lapp 2170353 is 1500 V.

Application range

- FOUNDATION™ Fieldbus is used in intrinsically safe areas, especially in the field of Process Automation
- Fixed installation

Product Make-up

- Lapp bus cables for FOUNDATION™ field bus are available in 4 versions:
- 3-core, unarmoured, with device ground
- 3-core, armoured (longitudinally welded, spiral corrugated copper sheath) with device ground
Yellow and blue version
- 2-core, not armoured, with device ground

In our Cable list on next page you can find all interesting information acc. article Lapp 2170353 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC BUS FF	Lapp 2170350	UNITRONIC® BUS FF 3	1x2x1.1 + 1x1.1 Ø	7.9	62.0	93
UNITRONIC BUS FF	Lapp 2170351	UNITRONIC® BUS FF 3 ARM (YE)	1x2x1.1 + 1x1.1 Ø	12.3	125.0	182
UNITRONIC BUS FF	Lapp 2170353	UNITRONIC® BUS FF 3 ARM (BU)	1x2x1.1 + 1x1.1 Ø	12.3	125.0	182
UNITRONIC BUS FF	Lapp 2170352	UNITRONIC® BUS FF 2	1 x 2 x 1,1	7.9	53.3	82