



**Description:** UNITRONIC BUS IS\_

**Lapp code:** Lapp 2170560

The **Test voltage** of the cable Lapp 2170560 is 0,5 mm - 2,5 mm<sup>2</sup> core / core = 1,5 kV 6 - 10 mm<sup>2</sup> core / core = 2,5 kV.

## Application range

- For outdoor applications
- Connection cable between tractor and pulled machinery

## Product Make-up

- 4x 0,5 mm<sup>2</sup> (red, yellow, black, green)
- 2x 2,5 mm<sup>2</sup> (red, black)
- 2x 6 mm<sup>2</sup> (red, black)
- Fine-wired copper conductor of bare copper strands in line with conductor class 5 acc. IEC 60228
- Outer Sheath: Black PVC or PUR special compound

In our Cable list on next page you can find all interesting information acc. article Lapp 2170560 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and cable diameter	Copper index (kg/km)
UNITRONIC BUS IS	Lapp 2170561	UNITRONIC® BUS IS PUR 2x6+2x2,5+1x4x0,5	2x6+2x2,5+1x4x0,5	182.4
UNITRONIC BUS IS	Lapp 2170560	UNITRONIC® BUS IS PVC 2x6+2x2,5+1x4x0,5	2x6+2x2,5+1x4x0,5	182.4