



**Description:** UNITRONIC BUS LD\_  
**Lapp code:** Lapp 2170203

The **Test voltage** of the cable Lapp 2170203 is Core/core: 1500 V rms.

## Application range

- For fixed installation  
Maximum electromagnetic screening
- Bus cables for bus systems such as e.g. Modbus, SUCOnet P, Modulink P, VariNet-P)
- Dry or damp rooms

## Product Make-up

- Stranded bare 7-wire conductor, colour-coded according to DIN 47100
- Copper braid
- PVC sheath
- Colour: violet (RAL 4001)
- UNITRONIC® BUS LD A as UNITRONIC® BUS LD, but with UL/CSA approval

In our Cable list on next page you can find all interesting information acc. article Lapp 2170203 and much more.

CABLE LIST - all informations you need you can find here

| Product Name                                 | Lapp Nr.     | Article designation | Number of pairs and mm <sup>2</sup> per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--|--------------|---------------------|---|---------------------|----------------------|----------------|
| for fixed installation                       |              |                     |   |                     |                      |                |
| UNITRONIC BUS LD                             | Lapp 2170203 | UNITRONIC® BUS LD   | 1 x 2 x 0,22                                      | 5.7                 | 18.0                 | 37             |
| UNITRONIC BUS LD                             | Lapp 2170204 | UNITRONIC® BUS LD   | 2 x 2 x 0,22                                      | 7.1                 | 28.0                 | 45             |
| UNITRONIC BUS LD                             | Lapp 2170205 | UNITRONIC® BUS LD   | 3 x 2 x 0,22                                      | 7.2                 | 37.0                 | 72             |
| For fixed installation - UL/CSA CMX approval |              |                     |   |                     |                      |                |
| UNITRONIC BUS LD                             | Lapp 2170803 | UNITRONIC® BUS LD A | 1 x 2 x 0,22                                      | 5.7                 | 18.0                 | 39             |