



**Description:** UNITRONIC BUS LD\_  
**Lapp code:** Lapp 2170205

The **Test voltage** of the cable Lapp 2170205 is Core/core: 1500 V rms.

## Application range

- For fixed installation  
Maximum electromagnetic screening
- Bus cables for bus systems such as e.g. Modbus, SUCOnet P, Modulink P, VariNet-P)
- Dry or damp rooms

## Product Make-up

- Stranded bare 7-wire conductor, colour-coded according to DIN 47100
- Copper braid
- PVC sheath
- Colour: violet (RAL 4001)
- UNITRONIC® BUS LD A as UNITRONIC® BUS LD, but with UL/CSA approval

In our Cable list on next page you can find all interesting information acc. article Lapp 2170205 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
for fixed installation						
UNITRONIC BUS LD	Lapp 2170203	UNITRONIC® BUS LD	1 x 2 x 0,22	5.7	18.0	37
UNITRONIC BUS LD	Lapp 2170204	UNITRONIC® BUS LD	2 x 2 x 0,22	7.1	28.0	45
UNITRONIC BUS LD	Lapp 2170205	UNITRONIC® BUS LD	3 x 2 x 0,22	7.2	37.0	72
For fixed installation - UL/CSA CMX approval						
UNITRONIC BUS LD	Lapp 2170803	UNITRONIC® BUS LD A	1 x 2 x 0,22	5.7	18.0	39