



**Description:** UNITRONIC BUS PB FD FRNC FC\_

**Lapp code:** Lapp 2170854

The **Test voltage** of the cable Lapp 2170854 is Core/core: 1500 V rms.

## Application range

- For highly flexible use in energy supply chains or permanently moving machines and linear robots
- This cable provides special advantages for use in sensitive areas where fire propagation must be avoided and the presence of toxic fumes would cause personal injury and damage to equipment.

## Product Make-up

- Stranded bare copper wire
- Foam Skin - core isolation (O2YS)
- Overall screening with copper braid and plastic-laminated aluminium foil
- Screening: wrapped with braided tinned-copper wires
- Outer sheath: PUR compound

In our Cable list on next page you can find all interesting information acc. article Lapp 2170854 and much more.

CABLE LIST - all informations you need you can find here

| Product Name                | Lapp Nr.     | Article designation          | Number of pairs and conductor diameter (mm) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-----------------------------|--------------|------------------------------|---|---------------------|----------------------|----------------|
| UNITRONIC BUS PB FD FRNC FC | Lapp 2170854 | UNITRONIC® BUS PB FD FRNC FC | 1x2x0,64                                    | 8.0                 | 26.0                 | 75             |