



Description: UNITRONIC BUS PB_
Lapp code: Lapp 2170820

The **Test voltage** of the cable Lapp 2170820 is Core/core: 1500 V rms.

Application range

- For fixed installation
Maximum electromagnetic screening
- Dry or damp rooms
- Item nos. 2170233, 2170333, 2170820, 2170824, 2170826 are all UV-resistant

Product Make-up

- FC: "Fast Connect" cable design
- P: Polyurethane
H: Halogen-free
- PE: polyethylene, black Outer sheath, e.g. for the food and beverage industry
- 7-W: 7-wire, e.g. for applications where vibrations occur
- COMBI: Data transmission and power supply in one cable

In our Cable list on next page you can find all interesting information acc. article Lapp 2170820 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and conductor diameter (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
For fixed installation - conventional cable assembly						
UNITRONIC BUS PB	Lapp 2170220	UNITRONIC® BUS PB	1 x 2 x 0,64	8.0	30.1	74
UNITRONIC BUS PB	Lapp 2170233	UNITRONIC® PB PE	1 x 2 x 0,64	8.0	30.1	57
UNITRONIC BUS PB	Lapp 2170226	UNITRONIC® BUS PB H 7-W	1 x 2 x 0,64	8.0	30.1	55
UNITRONIC BUS PB	Lapp 2170225	UNITRONIC® BUS PB COMBI 7-W	1 x 2 x 0,64 Ø + 3 x 1,0 mm ²	9.8	59.0	92
For fixed installation - UL/CSA CMX approval						
UNITRONIC BUS PB	Lapp 2170219	UNITRONIC® BUS PB A	1 x 2 x 0,64	8.0	30.1	57
For fixed installation - UL/CSA CMG approval						
UNITRONIC BUS PB	Lapp 2170824	UNITRONIC® BUS PB 7-W A	1 x 2 x 0,64	8.0	30.1	55
For fixed installation - "Fast Connect" cable assembly						
UNITRONIC BUS PB	Lapp 2170333	UNITRONIC® BUS PB PE FC	1 x 2 x 0,64	8.0	26.0	67
For fixed installation - UL/CSA CMX approval						
UNITRONIC BUS PB	Lapp 2170330	UNITRONIC® BUS PB P FC	1 x 2 x 0,64	8.0	26.0	71
For fixed installation - "Fast Connect" cable assembly - UL/CSA CMG approval						
UNITRONIC BUS PB	Lapp 2170820	UNITRONIC® BUS PB FC	1 x 2 x 0,64	8.0	26.0	84
UNITRONIC BUS PB	Lapp 2170826	UNITRONIC® BUS PB 7-W FC	1 x 2 x 0,64	8.0	26.0	67
UNITRONIC BUS PB	Lapp 2170326	UNITRONIC® BUS PB-H FC	1 x 2 x 0,64	8.0	26.0	72