



**Description:** UNITRONIC BUS PB ROBUST\_

**Lapp code:** Lapp 2170620

The **Test voltage** of the cable Lapp 2170620 is Core/core: 1500 V rms Core/screen: 1500 V.

## Application range

- For use for PROFIBUS-DP or FIP in harsh industrial environments
- Fixed installation

## Product Make-up

- Solid and bare copper conductor
- Foam Skin - core isolation (O2YS)
- Overall screening with copper braid and plastic-laminated aluminium foil
- Tin-plated copper wire braiding
- With conventional cable design, but with an outer sheath made of special TPE

In our Cable list on next page you can find all interesting information acc. article Lapp 2170620 and much more.

CABLE LIST - all informations you need you can find here

| Product Name            | Lapp Nr.     | Article designation      | Number of pairs and conductor diameter (mm) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|-------------------------|--------------|--------------------------|---|---------------------|----------------------|----------------|
| for fixed installation  |              |                          |   |                     |                      |                |
| UNITRONIC BUS PB ROBUST | Lapp 2170620 | UNITRONIC® BUS PB ROBUST | 1 x 2 x 0,64                                | 8.0                 | 26.0                 | 55             |