



Description: UNITRONIC BUS PB Y 7-W FC BK_

Lapp code: Lapp 2170310

The **Test voltage** of the cable Lapp 2170310 is Core/core: 1500 V rms Core/screen: 1500 V.

Application range

- PROFIBUS DP (in accordance with DIN 19245 and EN 50170, e.g. for SIEMENS SIMATIC® NET, also suitable for FIP - Factory Instrumentation Protocol).

Product Make-up

- Stranded conductor, 7-wire, bare
- Foam Skin - core isolation (O2YS)
- Overall screening with copper braid and plastic-laminated aluminium foil
- Tin-plated copper wire braiding
- PVC outer sheath, black

In our Cable list on next page you can find all interesting information acc. article Lapp 2170310 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Article designation | Number of pairs and conductor diameter (mm) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------|--------------|-------------------------------|---|---------------------|----------------------|----------------|
| UNITRONIC BUS PB Y 7-W FC BK | Lapp 2170310 | UNITRONIC® BUS PB Y 7-W FC BK | 1 x 2 x 0,64 | 7.8 | 30.1 | 80 |