



**Description:** UNITRONIC BUS SAFETY\_

**Lapp code:** Lapp 2170885

The **Test voltage** of the cable Lapp 2170885 is Core/core: 3000 V Core/core: 1500 V (FD- version).

## Application range

- For fixed installation and highly flexible applications
- For systems such as SafetyBUS p®, based on the well-known CAN bus system

## Product Make-up

- Stranded conductor, 3 cores twisted, colour-coded in accordance with DIN 47100 (white, brown, green), copper braiding, halogen-free outer sheath
- UNITRONIC® BUS SAFETY FD P is as per UNITRONIC® BUS SAFETY, but also suitable for highly flexible applications
- Flame-retardant according IEC 60332-1-2

In our Cable list on next page you can find all interesting information acc. article Lapp 2170885 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
for fixed installation						
UNITRONIC BUS SAFETY	Lapp 2170295	UNITRONIC® BUS SAFETY	3 x 0,75	7.6	49.0	68
For highly flexible applications (e.g. power chains)						
UNITRONIC BUS SAFETY	Lapp 2170885	UNITRONIC® BUS SAFETY FD P	3 x 0,75	7.8	49.0	68