



Description: UNITRONIC DeviceNet THICK + THIN_

Lapp code: Lapp 2170341

The **Test voltage** of the cable Lapp 2170341 is Core/core: 2000 V.

Application range

- Fixed installation
- DeviceNet™ connects industrial devices e.g. limit switches, photoelectric switches, valve islands, motor starters, drives, PLCs, etc.

Product Make-up

- Core insulation made of foam skin
- Outer sheath: Halogene free (FRNC) or Polyvinylchlorid (PVC)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170341 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/m)
Halogen-free						
UNITRONIC DeviceNet THICK + THIN	Lapp 2170340	UNITRONIC® BUS DN THICK FRNC	1x2xAWG18 + 1x2xAWG15	12.2	82.8	195
UNITRONIC DeviceNet THICK + THIN	Lapp 2170341	UNITRONIC® BUS DN THIN FRNC	1x2xAWG24 + 1x2xAWG22	6.9	33.4	69.5
With PVC outer sheath						
UNITRONIC DeviceNet THICK + THIN	Lapp 2170342	UNITRONIC® BUS DN THICK Y	1x2xAWG18 + 1x2xAWG15	12.2	88.4	192
UNITRONIC DeviceNet THICK + THIN	Lapp 2170343	UNITRONIC® BUS DN THIN Y	1x2xAWG24 + 1x2xAWG22	6.9	33.4	66.9