



Description: UNITRONIC EB CY (TP) 3 x 2 x 0,75_

Lapp code: Lapp 0012621

The **Test voltage** of the cable Lapp 0012621 is 2500 V.

Application range

- Reliable data transmission in intrinsically safe circuits
- In EMC-sensitive environments (electromagnetic compatibility)

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of PVC
- TP structure
- Tinned-copper braiding
- Outer sheath made of PVC
Outer sheath colour: sky blue (RAL 5015)

In our Cable list on next page you can find all interesting information acc. article Lapp 0012621 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of pairs and conductor cross section (mm ²) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------------|--------------|--|---------------------|----------------------|----------------|
| UNITRONIC® EB CY (TP) | | | | | |
| UNITRONIC EB CY (TP) 2 x 2 x 0,75 | Lapp 0012620 | 2 x 2 x 0,75 | 8.7 | 58.0 | 106 |
| UNITRONIC EB CY (TP) 3 x 2 x 0,75 | Lapp 0012621 | 3 x 2 x 0,75 | 9.6 | 84.0 | 140 |
| UNITRONIC EB CY (TP) 4 x 2 x 0,75 | Lapp 0012622 | 4 x 2 x 0,75 | 10.9 | 108.0 | 179 |
| UNITRONIC EB CY (TP) 6 x 2 x 0,75 | Lapp 0012624 | 6 x 2 x 0,75 | 12.3 | 146.0 | 246 |
| UNITRONIC EB CY (TP) 10 x 2 x 0,75 | Lapp 0012626 | 10 x 2 x 0,75 | 16.1 | 220.0 | 392 |