



Description: UNITRONIC FD CP plus 4 x 0,14_

Lapp code: Lapp 0028882

The **Test voltage** of the cable Lapp 0028882 is Core/core: 1500 V rms Core/screen: 500 V.

Application range

- Multifunctional-use, e.g. for packaging industry and storage and retrieval units
- Suitable for use in measuring, control and regulating circuits
- In power chains or moving machine parts
- For the North American market
- Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product Make-up

- Extra-fine wire strand made of bare copper wires
- Core insulation: Based on Polyolefin
- Tinned-copper braiding
- Non-woven wrapping
- Outer sheath made of special PUR compound
Outer sheath colour: grey (RAL 7001)

In our Cable list on next page you can find all interesting information acc. article Lapp 0028882 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------|--------------|---|---------------------|----------------------|----------------|
| UNITRONIC® FD CP plus | | | | | |
| UNITRONIC FD CP plus 2 x 0,14 | Lapp 0028880 | 2 x 0,14 | 4.3 | 11.2 | 33 |
| UNITRONIC FD CP plus 3 x 0,14 | Lapp 0028881 | 3 x 0,14 | 4.5 | 14.1 | 36 |
| UNITRONIC FD CP plus 4 x 0,14 | Lapp 0028882 | 4 x 0,14 | 4.8 | 15.5 | 40 |
| UNITRONIC FD CP plus 5 x 0,14 | Lapp 0028883 | 5 x 0,14 | 5.1 | 18.3 | 45 |
| UNITRONIC FD CP plus 7 x 0,14 | Lapp 0028884 | 7 x 0,14 | 5.7 | 27.8 | 67 |
| UNITRONIC FD CP plus 10 x 0,14 | Lapp 0028885 | 10 x 0,14 | 6.7 | 39.3 | 87 |
| UNITRONIC FD CP plus 14 x 0,14 | Lapp 0028886 | 14 x 0,14 | 6.8 | 45.3 | 102 |
| UNITRONIC FD CP plus 18 x 0,14 | Lapp 0028887 | 18 x 0,14 | 7.4 | 54.1 | 118 |
| UNITRONIC FD CP plus 25 x 0,14 | Lapp 0028888 | 25 x 0,14 | 8.9 | 68.4 | 157 |
| UNITRONIC FD CP plus 2 x 0,25 | Lapp 0028889 | 2 x 0,25 | 4.9 | 14.9 | 38 |
| UNITRONIC FD CP plus 3 x 0,25 | Lapp 0028890 | 3 x 0,25 | 5.1 | 18.8 | 45 |
| UNITRONIC FD CP plus 4 x 0,25 | Lapp 0028891 | 4 x 0,25 | 5.5 | 21.3 | 52 |
| UNITRONIC FD CP plus 5 x 0,25 | Lapp 0028892 | 5 x 0,25 | 5.9 | 31.0 | 69 |
| UNITRONIC FD CP plus 7 x 0,25 | Lapp 0028893 | 7 x 0,25 | 6.7 | 39.6 | 84 |
| UNITRONIC FD CP plus 10 x 0,25 | Lapp 0028894 | 10 x 0,25 | 8.2 | 53.9 | 109 |
| UNITRONIC FD CP plus 14 x 0,25 | Lapp 0028895 | 14 x 0,25 | 8.3 | 64.2 | 136 |
| UNITRONIC FD CP plus 18 x 0,25 | Lapp 0028896 | 18 x 0,25 | 9.1 | 78.4 | 161 |
| UNITRONIC FD CP plus 25 x 0,25 | Lapp 0028897 | 25 x 0,25 | 11.0 | 101.0 | 213 |
| UNITRONIC FD CP plus 2 x 0,34 | Lapp 0028898 | 2 x 0,34 | 5.3 | 18.1 | 45 |
| UNITRONIC FD CP plus 3 x 0,34 | Lapp 0028899 | 3 x 0,34 | 5.6 | 28.7 | 61 |
| UNITRONIC FD CP plus 4 x 0,34 | Lapp 0028900 | 4 x 0,34 | 6.0 | 35.7 | 77 |
| UNITRONIC FD CP plus 5 x 0,34 | Lapp 0028901 | 5 x 0,34 | 6.5 | 39.1 | 83 |
| UNITRONIC FD CP plus 7 x 0,34 | Lapp 0028902 | 7 x 0,34 | 7.4 | 52.7 | 109 |
| UNITRONIC FD CP plus 10 x 0,34 | Lapp 0028903 | 10 x 0,34 | 9.1 | 67.4 | 147 |

UNITRONIC FD CP plus 4 x 0,14_

Lapp 0028882



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|--------------------------------|--------------|---|---------------------|----------------------|----------------|
| UNITRONIC FD CP plus 14 x 0,34 | Lapp 0028904 | 14 x 0,34 | 9.2 | 85.8 | 186 |
| UNITRONIC FD CP plus 18 x 0,34 | Lapp 0028905 | 18 x 0,34 | 10.3 | 99.7 | 216 |
| UNITRONIC FD CP plus 25 x 0,34 | Lapp 0028906 | 25 x 0,34 | 12.5 | 155.0 | 314 |