



**Description:** UNITRONIC LAN 1000 S-FTP Cat.7\_

**Lapp code:** Lapp 2170614

The **Test voltage** of the cable Lapp 2170614 is /.

## Application range

- Mainly used where the terminal density is very high, e.g. for wiring office, administration and development buildings in the tertiary area (floor wiring).
- Cable length in tertiary area (horizontal area, floor) should not exceed a length of 100 m in accordance with the ISO/IEC 11801 and EN 50173 standards (90 m in cable duct + 10 m in working area)

## Product Make-up

- S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
- Solid conductor
- Outer sheath: halogen-free, flame-retardant compound
- Colour: yellow (RAL 7032)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170614 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Halogen-free versions						
UNITRONIC LAN 1000 S/FTP Cat.7	Lapp 2170614	1000 S/FTP Cat.7 LSZH	4 x 2 x AWG23/1	7,7	27.0	60
UNITRONIC LAN 1000 S/FTP Cat.7	Lapp 2170634	1000 S/FTP Cat.7 duplex	2 x (4 x 2 x AWG23/1)	7,7 x 15,4	54.0	120