



Description: UNITRONIC LAN 1200 S-FTP Cat.7A_

Lapp code: Lapp 2170618

The **Test voltage** of the cable Lapp 2170618 is /.

Application range

- Mainly used where the terminal density is very high, e.g. for wiring office, administration and development buildings in the tertiary area (floor wiring).
- Cable length in tertiary area (horizontal area, floor) should not exceed a length of 100 m in accordance with the ISO/IEC 11801 and EN 50173 standards (90 m in cable duct + 10 m in working area)

Product Make-up

- Solid bare copper wire AWG22
- Cellular polyolefin core insulation, max. core diameter 1.6 mm
- Pair screen made of aluminium-lined plastic foil, overall screening made of tinned-copper braiding
- Outer sheath: halogen-free, flame-retardant compound
- Colour: yellow (RAL 7032)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170618 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC LAN 1200 S/FTP Cat.7A	Lapp 2170615	1200 S/FTP Cat.7A LSZH	4 x 2 x AWG22/1	8,1	34.0	66
UNITRONIC LAN 1200 S/FTP Cat.7A	Lapp 2170618	1200 S/FTP Cat.7A LSZH duplex	4 x 2 x AWG22	16,3	68.0	