



Description: UNITRONIC LAN 200 - Cat.5e_

Lapp code: Lapp 2170126

The **Test voltage** of the cable Lapp 2170126 is /.

Application range

- Mainly used where the terminal density is very high, e.g. for wiring office, administration and development buildings in the tertiary area (floor wiring).
- Cable length in tertiary area (horizontal area, floor) should not exceed a length of 100 m in accordance with the ISO/IEC 11801 and EN 50173 standards (90 m in cable duct + 10 m in working area)

Product Make-up

- U/UTP: no overall or pair shielding
- F/UTP: foil screening as overall screening
- SF/UTP: copper braid and foil screening as overall screening
- Solid conductor
- outer sheath either as PVC or LSZH (color grey RAL 7035)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170126 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
PVC version						
UNITRONIC LAN 200 - Cat.5e	Lapp 2170125	200 U/UTP Cat.5e	4 x 2 x AWG24/1	5,6	17.0	33
UNITRONIC LAN 200 - Cat.5e	Lapp 2170126	200 F/UTP Cat.5e	4 x 2 x AWG24/1	6,4	18.0	39
UNITRONIC LAN 200 - Cat.5e	Lapp 2170128	200 SF/UTP Cat.5e	4 x 2 x AWG24/1	6,7	32.0	49
Halogen-free versions						
UNITRONIC LAN 200 - Cat.5e	Lapp 2170173	200 U/UTP Cat.5e LSZH	4 x 2 x AWG24/1	5,6	17.0	33
UNITRONIC LAN 200 - Cat.5e	Lapp 2170138	200 SF/UTP Cat.5e LSZH	4 x 2 x AWG24/1	6,7	32.0	49