



**Description:** UNITRONIC LAN 250 - Cat.6\_

**Lapp code:** Lapp 2170171

The **Test voltage** of the cable Lapp 2170171 is /.

## Application range

- Mainly used where the terminal density is very high, e.g. for wiring office, administration and development buildings in the tertiary area (floor wiring).

## Product Make-up

- U/UTP: no overall or pair shielding
- F/UTP: foil screening as overall screening
- Solid conductor
- outer sheath either as PVC (color grey RAL1015) or LSZH (color orange RAL2003)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170171 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
PVC versions						
UNITRONIC LAN 250 - Cat.6	Lapp 2170186	250 U/UTP Cat.6	4 x 2 x AWG24/1	6,5	18.0	46
Halogen-free versions						
UNITRONIC LAN 250 - Cat.6	Lapp 2170171	250 U/UTP Cat.6 LSZH	4 x 2 x AWG24/1	6,5	18.0	46
UNITRONIC LAN 250 - Cat.6	Lapp 2170170	250 F/UTP Cat.6 LSZH	4 x 2 x AWG24/1	7,5	19.0	54