



Description: UNITRONIC LAN FLEX_

Lapp code: Lapp 2170129

The **Test voltage** of the cable Lapp 2170129 is /.

Application range

- Indoor applications
- LAN connections
- Control cabinet wiring

Product Make-up

- F/UTP: foil screening as overall screening
- SF/UTP: copper braid and foil screening as overall screening
- S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
- outer sheath either as PVC or LSZH (color grey RAL 7035)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170129 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
PVC versions						
UNITRONIC LAN FLEX	Lapp 2170127	200 F/UTP Cat.5e	4 x 2 x AWG26/7	5,6	13.0	28
UNITRONIC LAN FLEX	Lapp 2170129	200 SF/UTP Cat.5e	4 x 2 x AWG26/7	6.0	22.0	36
UNITRONIC LAN FLEX	Lapp 2170144	600 S/FTP CAT7 Y	4 x 2 x AWG26/7	6,5	22.0	39
Halogen-free versions						
UNITRONIC LAN FLEX	Lapp 2170172	200 F/UTP Cat.5e LSZH	4 x 2 x AWG26/7	5,6	13.0	28
UNITRONIC LAN FLEX	Lapp 2170139	200 SF/UTP Cat.5e LSZH	4 x 2 x AWG26/7	6.0	22.0	36
UNITRONIC LAN FLEX	Lapp 2170142	600 S/FTP CAT7 LSZH	4 x 2 x AWG26/7	6,2	21.0	40