



**Description:** UNITRONIC LAN OUTDOOR\_

**Lapp code:** Lapp 2170197

The **Test voltage** of the cable Lapp 2170197 is /.

## Application range

- For outdoor use
- Suitable for direct burial
- Cable length in tertiary area (horizontal area, floor) should not exceed a length of 100 m in accordance with the ISO/IEC 11801 and EN 50173 standards (90 m in cable duct + 10 m in working area)

## Product Make-up

- S/FTP: copper braid as overall screening and pair screening with aluminium compound foil
- Solid conductor
- Core insulation: foamed polyolefin
- PE outer sheath
- Colour: black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 2170197 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Article designation	Number of pairs and AWG per conductor	Max. outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Suitable for direct burial						
UNITRONIC LAN OUTDOOR	Lapp 2170198	1000 S/FTP Cat.7 (L)PE	4 x 2 x AWG23/1	10.0	34.0	90
Suitable for direct routing underground, not transversely waterproof						
UNITRONIC LAN OUTDOOR	Lapp 2170197	1000 S/FTP Cat.7 PE	4 x 2 x AWG23/1	9,6	34.0	75