



Description: UNITRONIC Li2YCY (TP) fine-wire 5 x 2 x 0,25_

Lapp code: Lapp 0031373

The **Test voltage** of the cable Lapp 0031373 is Core/core: 2000 V Core/screen: 1000 V.

Application range

- Particularly suitable for wiring data systems with transmission rates up to 10 Megabits per second, and is qualified for the RS422 and RS485 interfaces.
- For fixed and limited flexible installation
- Can be used in dry or damp rooms
- Signal-, control- and measuring cable, for transmission of low, sensitive signals and high bit rates
- UNITRONIC® Li2YCYv (TP) with reinforced black outer sheath (Yv) is suitable for indoors and outdoors, as well as direct burial in the ground

Product Make-up

- Similar to UNITRONIC® Li2YCY (TP), but with fine-wire conductor design

In our Cable list on next page you can find all interesting information acc. article Lapp 0031373 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of pairs and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® Li2YCY (TP) fine-wire					
UNITRONIC Li2YCY (TP) fine-wire 1 x 2 x 0,25	Lapp 0031370	1 x 2 x 0,25	5.7	14.0	38
UNITRONIC Li2YCY (TP) fine-wire 2 x 2 x 0,25	Lapp 0031371	2 x 2 x 0,25	6.9	28.0	56
UNITRONIC Li2YCY (TP) fine-wire 3 x 2 x 0,25	Lapp 0031372	3 x 2 x 0,25	7.5	39.6	64
UNITRONIC Li2YCY (TP) fine-wire 5 x 2 x 0,25	Lapp 0031373	5 x 2 x 0,25	8.3	50.0	93