



Description: UNITRONIC LiFYCY (TP) 8 x 2 x 0,08_

Lapp code: Lapp 0034233

The **Test voltage** of the cable Lapp 0034233 is 800 V.

Application range

- For protection against high-frequency interference, screened, fine-wire cables are used in many devices.
- Wherever screened cables with smallest dimensions are required
- Examples: microelectronics, hearing aids etc.

Product Make-up

- Extra-fine wire strand made of bare copper wires
- Core insulation made of PVC
- TP structure
- Tinned-copper braiding
- Outer sheath made of PVC
Outer sheath colour: pebble grey (RAL 7032)

In our Cable list on next page you can find all interesting information acc. article Lapp 0034233 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of pairs and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® LiFYCY (TP)					
UNITRONIC LiFYCY (TP) 4 x 2 x 0,08	Lapp 0034231	4 x 2 x 0,08	5.1	19.4	37
UNITRONIC LiFYCY (TP) 8 x 2 x 0,08	Lapp 0034233	8 x 2 x 0,08	6.7	23.7	76