



Description: UNITRONIC LiYCY-CY 5 x 0,25_

Lapp code: Lapp 0032305

The **Test voltage** of the cable Lapp 0032305 is 1200 V.

Application range

- When a lossless transmission of data has to be guaranteed in fields with strong interference, cables with individually-screened cores and an additional overall screening are used
- Dry or damp rooms

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of PVC
- Tinned-copper braiding for each core
- Inner sheath made of PVC over each screened core
- Tinned-copper braiding
- Outer sheath made of PVC
Outer sheath colour: pebble grey (RAL 7032)

In our Cable list on next page you can find all interesting information acc. article Lapp 0032305 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® LiYCY-CY					
UNITRONIC LiYCY-CY 2 x 0,25	Lapp 0032302	2 x 0,25	6.9	41.5	69
UNITRONIC LiYCY-CY 3 x 0,25	Lapp 0032303	3 x 0,25	7.2	53.0	106
UNITRONIC LiYCY-CY 4 x 0,25	Lapp 0032304	4 x 0,25	7.8	65.0	130
UNITRONIC LiYCY-CY 5 x 0,25	Lapp 0032305	5 x 0,25	8.5	78.0	161
UNITRONIC LiYCY-CY 7 x 0,25	Lapp 0032307	7 x 0,25	9.2	94.0	196