



**Description:** UNITRONIC LiYCY (TP) A 10 x 2 x AWG26-7\_

**Lapp code:** Lapp 0066210

The **Test voltage** of the cable Lapp 0066210 is 1500 V.

## Application range

- For the North American market
- Wiring of devices, machines and plants intended for export to the North American market or countries where UL-/CSA approved cables are used.

## Product Make-up

- Multi-wire strand made of tinned copper wires
- Core insulation made of PVC
- TP structure
- Tinned-copper braiding
- Outer sheath made of special PVC compound  
Outer sheath colour: dark grey (RAL 7005)

In our Cable list on next page you can find all interesting information acc. article Lapp 0066210 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and AWG per conductor	Number of pairs and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® LiYCY (TP) A						
UNITRONIC LiYCY (TP) A 2 x 2 x AWG26/7	Lapp 0066202	2 x 2 x AWG26/7	2 x 2 x 0,14	5.5	18.0	45.9
UNITRONIC LiYCY (TP) A 4 x 2 x AWG26/7	Lapp 0066204	4 x 2 x AWG26/7	4 x 2 x 0,14	6.4	24.0	58
UNITRONIC LiYCY (TP) A 5 x 2 x AWG26/7	Lapp 0066205	5 x 2 x AWG26/7	5 x 2 x 0,14	6.6	30.0	58
UNITRONIC LiYCY (TP) A 8 x 2 x AWG26/7	Lapp 0066208	8 x 2 x AWG26/7	8 x 2 x 0,14	7.9	53.0	85
UNITRONIC LiYCY (TP) A 10 x 2 x AWG26/7	Lapp 0066210	10 x 2 x AWG26/7	10 x 2 x 0,14	8.7	55.0	106
UNITRONIC LiYCY (TP) A 12 x 2 x AWG26/7	Lapp 0066212	12 x 2 x AWG26/7	12 x 2 x 0,14	8.9	64.0	113
UNITRONIC LiYCY (TP) A 16 x 2 x AWG26/7	Lapp 0066216	16 x 2 x AWG26/7	16 x 2 x 0,14	10.2	87.0	149
UNITRONIC LiYCY (TP) A 2 x 2 x AWG24/7	Lapp 0066232	2 x 2 x AWG24/7	2 x 2 x 0,23	6.1	24.5	57
UNITRONIC LiYCY (TP) A 3 x 2 x AWG24/7	Lapp 0066233	3 x 2 x AWG24/7	3 x 2 x 0,23	6.7	28.9	62
UNITRONIC LiYCY (TP) A 4 x 2 x AWG24/7	Lapp 0066234	4 x 2 x AWG24/7	4 x 2 x 0,23	7.2	33.5	70
UNITRONIC LiYCY (TP) A 5 x 2 x AWG24/7	Lapp 0066235	5 x 2 x AWG24/7	5 x 2 x 0,23	7.5	46.3	91
UNITRONIC LiYCY (TP) A 2 x 2 x AWG22/7	Lapp 0066238	2 x 2 x AWG22/7	2 x 2 x 0,34	7.4	38.0	45
UNITRONIC LiYCY (TP) A 3 x 2 x AWG22/7	Lapp 0066239	3 x 2 x AWG22/7	3 x 2 x 0,34	8.1	45.1	64
UNITRONIC LiYCY (TP) A 4 x 2 x AWG22/7	Lapp 0066240	4 x 2 x AWG22/7	4 x 2 x 0,34	8.8	54.6	75
UNITRONIC LiYCY (TP) A 2 x 2 x AWG20/7	Lapp 0066242	2 x 2 x AWG20/7	2 x 2 x 0,5	8.2	49.7	93
UNITRONIC LiYCY (TP) A 3 x 2 x AWG20/7	Lapp 0066243	3 x 2 x AWG20/7	3 x 2 x 0,5	9.1	60.1	102
UNITRONIC LiYCY (TP) A 4 x 2 x AWG20/7	Lapp 0066244	4 x 2 x AWG20/7	4 x 2 x 0,5	10.2	78.7	120

**UNITRONIC LiYCY (TP) A 10 x 2 x AWG26-7\_**

Lapp 0066210



Product Name	Lapp Nr.	Number of cores and AWG per conductor	Number of pairs and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC LiYCY (TP) A 2 x 2 x AWG19/19	Lapp 0066262	2 x 2 x AWG19/19	2 x 2 x 0,75	8.7	65.2	140