



Description: UNITRONIC LiYCY (TP) A 5 x 2 x AWG24-7_

Lapp code: Lapp 0066235

The **Test voltage** of the cable Lapp 0066235 is 1500 V.

Application range

- For the North American market
- Wiring of devices, machines and plants intended for export to the North American market or countries where UL-/CSA approved cables are used.

Product Make-up

- Multi-wire strand made of tinned copper wires
- Core insulation made of PVC
- TP structure
- Tinned-copper braiding
- Outer sheath made of special PVC compound
Outer sheath colour: dark grey (RAL 7005)

In our Cable list on next page you can find all interesting information acc. article Lapp 0066235 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and AWG per conductor | Number of pairs and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---|--------------|---------------------------------------|---|---------------------|----------------------|----------------|
| UNITRONIC® LiYCY (TP) A | | | | | | |
| UNITRONIC LiYCY (TP) A 2 x 2 x AWG26/7 | Lapp 0066202 | 2 x 2 x AWG26/7 | 2 x 2 x 0,14 | 5.5 | 18.0 | 45.9 |
| UNITRONIC LiYCY (TP) A 4 x 2 x AWG26/7 | Lapp 0066204 | 4 x 2 x AWG26/7 | 4 x 2 x 0,14 | 6.4 | 24.0 | 58 |
| UNITRONIC LiYCY (TP) A 5 x 2 x AWG26/7 | Lapp 0066205 | 5 x 2 x AWG26/7 | 5 x 2 x 0,14 | 6.6 | 30.0 | 58 |
| UNITRONIC LiYCY (TP) A 8 x 2 x AWG26/7 | Lapp 0066208 | 8 x 2 x AWG26/7 | 8 x 2 x 0,14 | 7.9 | 53.0 | 85 |
| UNITRONIC LiYCY (TP) A 10 x 2 x AWG26/7 | Lapp 0066210 | 10 x 2 x AWG26/7 | 10 x 2 x 0,14 | 8.7 | 55.0 | 106 |
| UNITRONIC LiYCY (TP) A 12 x 2 x AWG26/7 | Lapp 0066212 | 12 x 2 x AWG26/7 | 12 x 2 x 0,14 | 8.9 | 64.0 | 113 |
| UNITRONIC LiYCY (TP) A 16 x 2 x AWG26/7 | Lapp 0066216 | 16 x 2 x AWG26/7 | 16 x 2 x 0,14 | 10.2 | 87.0 | 149 |
| UNITRONIC LiYCY (TP) A 2 x 2 x AWG24/7 | Lapp 0066232 | 2 x 2 x AWG24/7 | 2 x 2 x 0,23 | 6.1 | 24.5 | 57 |
| UNITRONIC LiYCY (TP) A 3 x 2 x AWG24/7 | Lapp 0066233 | 3 x 2 x AWG24/7 | 3 x 2 x 0,23 | 6.7 | 28.9 | 62 |
| UNITRONIC LiYCY (TP) A 4 x 2 x AWG24/7 | Lapp 0066234 | 4 x 2 x AWG24/7 | 4 x 2 x 0,23 | 7.2 | 33.5 | 70 |
| UNITRONIC LiYCY (TP) A 5 x 2 x AWG24/7 | Lapp 0066235 | 5 x 2 x AWG24/7 | 5 x 2 x 0,23 | 7.5 | 46.3 | 91 |
| UNITRONIC LiYCY (TP) A 2 x 2 x AWG22/7 | Lapp 0066238 | 2 x 2 x AWG22/7 | 2 x 2 x 0,34 | 7.4 | 38.0 | 45 |
| UNITRONIC LiYCY (TP) A 3 x 2 x AWG22/7 | Lapp 0066239 | 3 x 2 x AWG22/7 | 3 x 2 x 0,34 | 8.1 | 45.1 | 64 |
| UNITRONIC LiYCY (TP) A 4 x 2 x AWG22/7 | Lapp 0066240 | 4 x 2 x AWG22/7 | 4 x 2 x 0,34 | 8.8 | 54.6 | 75 |
| UNITRONIC LiYCY (TP) A 2 x 2 x AWG20/7 | Lapp 0066242 | 2 x 2 x AWG20/7 | 2 x 2 x 0,5 | 8.2 | 49.7 | 93 |
| UNITRONIC LiYCY (TP) A 3 x 2 x AWG20/7 | Lapp 0066243 | 3 x 2 x AWG20/7 | 3 x 2 x 0,5 | 9.1 | 60.1 | 102 |
| UNITRONIC LiYCY (TP) A 4 x 2 x AWG20/7 | Lapp 0066244 | 4 x 2 x AWG20/7 | 4 x 2 x 0,5 | 10.2 | 78.7 | 120 |

UNITRONIC LiYCY (TP) A 5 x 2 x AWG24-7_

Lapp 0066235



| Product Name | Lapp Nr. | Number of cores and AWG per conductor | Number of pairs and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|---|--------------|---------------------------------------|---|---------------------|----------------------|----------------|
| UNITRONIC LiYCY (TP) A 2 x 2 x AWG19/19 | Lapp 0066262 | 2 x 2 x AWG19/19 | 2 x 2 x 0,75 | 8.7 | 65.2 | 140 |