



**Description:** UNITRONIC LiYD11Y 12 x 0,25\_

**Lapp code:** Lapp 0033312

The **Test voltage** of the cable Lapp 0033312 is 1200 V.

## Application range

- Intended for use in industrial environments, where cables should have excellent mechanical and chemical resistance.
- Screened cables with small dimensions are suitable for use in computer systems, instrumentation technology, office equipment, balances.
- Can be used in dry or damp rooms
- Outdoor use is possible within the indicated operating temperature range

## Product Make-up

- Extra-fine wire strand made of bare copper wires
- Core insulation made of PVC
- Screening: wrapped with bare copper wires
- Outer sheath made of PUR  
Outer sheath colour: black (RAL 9005)

In our Cable list on next page you can find all interesting information acc. article Lapp 0033312 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® LiYD11Y					
UNITRONIC LiYD11Y 2 x 0,14	Lapp 0033202	2 x 0,14	4.1	9.6	20
UNITRONIC LiYD11Y 3 x 0,14	Lapp 0033203	3 x 0,14	4.3	11.0	25
UNITRONIC LiYD11Y 4 x 0,14	Lapp 0033204	4 x 0,14	4.5	12.0	27
UNITRONIC LiYD11Y 5 x 0,14	Lapp 0033205	5 x 0,14	4.8	14.4	33
UNITRONIC LiYD11Y 6 x 0,14	Lapp 0033206	6 x 0,14	5.5	17.6	38
UNITRONIC LiYD11Y 7 x 0,14	Lapp 0033207	7 x 0,14	5.9	21.5	41
UNITRONIC LiYD11Y 12 x 0,14	Lapp 0033212	12 x 0,14	7.2	33.2	62
UNITRONIC LiYD11Y 18 x 0,14	Lapp 0033218	18 x 0,14	8.0	44.2	83
UNITRONIC LiYD11Y 2 x 0,25	Lapp 0033302	2 x 0,25	4.7	11.8	25
UNITRONIC LiYD11Y 3 x 0,25	Lapp 0033303	3 x 0,25	5.3	15.6	31
UNITRONIC LiYD11Y 4 x 0,25	Lapp 0033304	4 x 0,25	5.6	18.2	36
UNITRONIC LiYD11Y 5 x 0,25	Lapp 0033305	5 x 0,25	6.0	21.4	42
UNITRONIC LiYD11Y 6 x 0,25	Lapp 0033306	6 x 0,25	6.8	26.1	49
UNITRONIC LiYD11Y 12 x 0,25	Lapp 0033312	12 x 0,25	8.4	48.1	81