



Description: UNITRONIC PUR CP (TP) 3 x 2 x 0,25_

Lapp code: Lapp 0032851

The **Test voltage** of the cable Lapp 0032851 is At 0.14 mm²: 1200 V ? 0.25 mm²: 1500 V.

Application range

- For harsh environmental conditions where robust and screened cables with small dimensions are necessary

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of PVC
- TP structure
- Tinned-copper braiding
- Outer sheath made of PUR
Outer sheath colour: pebble grey (RAL 7032)

In our Cable list on next page you can find all interesting information acc. article Lapp 0032851 and much more.

CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of pairs and conductor cross section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® PUR CP (TP)					
UNITRONIC PUR CP (TP) 2 x 2 x 0,25	Lapp 0032850	2 x 2 x 0,25	6.3	28.0	54
UNITRONIC PUR CP (TP) 3 x 2 x 0,25	Lapp 0032851	3 x 2 x 0,25	7.1	40.0	66
UNITRONIC PUR CP (TP) 4 x 2 x 0,25	Lapp 0032852	4 x 2 x 0,25	7.6	45.0	81
UNITRONIC PUR CP (TP) 6 x 2 x 0,25	Lapp 0032854	6 x 2 x 0,25	8.5	70.0	115
UNITRONIC PUR CP (TP) 2 x 2 x 0,5	Lapp 0032860	2 x 2 x 0,5	8.6	48.0	93
UNITRONIC PUR CP (TP) 3 x 2 x 0,5	Lapp 0032861	3 x 2 x 0,5	8.7	74.0	129
UNITRONIC PUR CP (TP) 4 x 2 x 0,5	Lapp 0032862	4 x 2 x 0,5	9.4	82.0	146
UNITRONIC PUR CP (TP) 6 x 2 x 0,5	Lapp 0032864	6 x 2 x 0,5	11.1	110.0	198
UNITRONIC PUR CP (TP) 4 x 2 x 0,75	Lapp 0032872	4 x 2 x 0,75	10.7	108.0	179
UNITRONIC PUR CP (TP) 5 x 2 x 0,75	Lapp 0032873	5 x 2 x 0,75	11.1	126.0	215