



Description: UNITRONIC PUR CP (TP) 6 x 2 x 0,5_

Lapp code: Lapp 0032864

The **Test voltage** of the cable Lapp 0032864 is At 0.14 mm²: 1200 V ? 0.25 mm²: 1500 V.

Application range

- For harsh environmental conditions where robust and screened cables with small dimensions are necessary

Product Make-up

- Fine-wire strand made of bare copper wires
- Core insulation made of PVC
- TP structure
- Tinned-copper braiding
- Outer sheath made of PUR
Outer sheath colour: pebble grey (RAL 7032)

In our Cable list on next page you can find all interesting information acc. article Lapp 0032864 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of pairs and conductor cross section (mm ²) | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------------|--------------|--|---------------------|----------------------|----------------|
| UNITRONIC® PUR CP (TP) | | | | | |
| UNITRONIC PUR CP (TP) 2 x 2 x 0,25 | Lapp 0032850 | 2 x 2 x 0,25 | 6.3 | 28.0 | 54 |
| UNITRONIC PUR CP (TP) 3 x 2 x 0,25 | Lapp 0032851 | 3 x 2 x 0,25 | 7.1 | 40.0 | 66 |
| UNITRONIC PUR CP (TP) 4 x 2 x 0,25 | Lapp 0032852 | 4 x 2 x 0,25 | 7.6 | 45.0 | 81 |
| UNITRONIC PUR CP (TP) 6 x 2 x 0,25 | Lapp 0032854 | 6 x 2 x 0,25 | 8.5 | 70.0 | 115 |
| UNITRONIC PUR CP (TP) 2 x 2 x 0,5 | Lapp 0032860 | 2 x 2 x 0,5 | 8.6 | 48.0 | 93 |
| UNITRONIC PUR CP (TP) 3 x 2 x 0,5 | Lapp 0032861 | 3 x 2 x 0,5 | 8.7 | 74.0 | 129 |
| UNITRONIC PUR CP (TP) 4 x 2 x 0,5 | Lapp 0032862 | 4 x 2 x 0,5 | 9.4 | 82.0 | 146 |
| UNITRONIC PUR CP (TP) 6 x 2 x 0,5 | Lapp 0032864 | 6 x 2 x 0,5 | 11.1 | 110.0 | 198 |
| UNITRONIC PUR CP (TP) 4 x 2 x 0,75 | Lapp 0032872 | 4 x 2 x 0,75 | 10.7 | 108.0 | 179 |
| UNITRONIC PUR CP (TP) 5 x 2 x 0,75 | Lapp 0032873 | 5 x 2 x 0,75 | 11.1 | 126.0 | 215 |