



**Description:** UNITRONIC ROBUST 5 x 0,34\_

**Lapp code:** Lapp 1032028

The **Test voltage** of the cable Lapp 1032028 is At 0.14 mm<sup>2</sup>: 1200 V ? 0.25 mm<sup>2</sup>: 1500 V.

## Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- For data processing, measurement and control engineering, safety related systems and as electronics cable
- For indoor and outdoor use

## Product Make-up

- Fine-wire/multi-wire (0.34 mm<sup>2</sup>) strand made of bare copper wires
- Core insulation made of special halogen-free compound
- Outer sheath made of special TPE
- Outer sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 1032028 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® ROBUST					
UNITRONIC ROBUST 2 x 0,14	Lapp 1032000	2 x 0,14	3.2	2.8	15
UNITRONIC ROBUST 3 x 0,14	Lapp 1032001	3 x 0,14	3.4	4.2	17
UNITRONIC ROBUST 4 x 0,14	Lapp 1032002	4 x 0,14	3.6	5.6	21
UNITRONIC ROBUST 5 x 0,14	Lapp 1032003	5 x 0,14	3.9	7.0	25
UNITRONIC ROBUST 7 x 0,14	Lapp 1032004	7 x 0,14	4.2	9.8	30
UNITRONIC ROBUST 8 x 0,14	Lapp 1032005	8 x 0,14	4.9	11.2	40
UNITRONIC ROBUST 10 x 0,14	Lapp 1032006	10 x 0,14	5.2	14.0	41
UNITRONIC ROBUST 12 x 0,14	Lapp 1032007	12 x 0,14	5.6	16.8	50
UNITRONIC ROBUST 16 x 0,14	Lapp 1032009	16 x 0,14	6.1	22.4	63
UNITRONIC ROBUST 25 x 0,14	Lapp 1032011	25 x 0,14	7.7	35.0	95
UNITRONIC ROBUST 2 x 0,25	Lapp 1032012	2 x 0,25	3.8	4.8	21
UNITRONIC ROBUST 3 x 0,25	Lapp 1032013	3 x 0,25	4.0	7.2	25
UNITRONIC ROBUST 4 x 0,25	Lapp 1032014	4 x 0,25	4.3	9.6	31
UNITRONIC ROBUST 5 x 0,25	Lapp 1032015	5 x 0,25	4.7	12.0	38
UNITRONIC ROBUST 7 x 0,25	Lapp 1032016	7 x 0,25	5.1	16.8	47
UNITRONIC ROBUST 8 x 0,25	Lapp 1032017	8 x 0,25	6.2	19.2	66
UNITRONIC ROBUST 10 x 0,25	Lapp 1032018	10 x 0,25	6.8	24.0	71
UNITRONIC ROBUST 12 x 0,25	Lapp 1032019	12 x 0,25	7.0	28.8	81
UNITRONIC ROBUST 16 x 0,25	Lapp 1032021	16 x 0,25	7.7	38.4	104
UNITRONIC ROBUST 25 x 0,25	Lapp 1032024	25 x 0,25	9.5	60.0	151
UNITRONIC ROBUST 2 x 0,34	Lapp 1032025	2 x 0,34	4.2	6.5	29
UNITRONIC ROBUST 3 x 0,34	Lapp 1032026	3 x 0,34	4.4	9.8	32
UNITRONIC ROBUST 4 x 0,34	Lapp 1032027	4 x 0,34	4.8	13.1	41
UNITRONIC ROBUST 5 x 0,34	Lapp 1032028	5 x 0,34	5.5	16.3	52

**UNITRONIC ROBUST 5 x 0,34\_**

Lapp 1032028



Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC ROBUST 7 x 0,34	Lapp 1032030	7 x 0,34	5.9	22.9	65
UNITRONIC ROBUST 8 x 0,34	Lapp 1032031	8 x 0,34	7.1	26.1	90
UNITRONIC ROBUST 10 x 0,34	Lapp 1032032	10 x 0,34	7.6	32.6	93
UNITRONIC ROBUST 12 x 0,34	Lapp 1032033	12 x 0,34	7.8	39.2	107
UNITRONIC ROBUST 16 x 0,34	Lapp 1032035	16 x 0,34	8.7	52.2	138
UNITRONIC ROBUST 15 x 0,34	Lapp 1032038	15 x 0,34	11.2	81.6	213