



Description: UNITRONIC ROBUST C 10 x 0,25_

Lapp code: Lapp 1032069

The **Test voltage** of the cable Lapp 1032069 is At 0.14 mm²: 1200 V ? 0.25 mm²: 1500 V.

Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- For data processing, measurement and control engineering, safety related systems and as electronics cable
- For indoor and outdoor use

Product Make-up

- Fine-wire/multi-wire (0.34 mm²) strand made of bare copper wires
- Core insulation made of special halogen-free compound
- Tinned-copper braiding
- Outer sheath made of special TPE
- Outer sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 1032069 and much more.

CABLE LIST - all informations you need you can find here

| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------|--------------|---|---------------------|----------------------|----------------|
| UNITRONIC® ROBUST C | | | | | |
| UNITRONIC ROBUST C 2 x 0,14 | Lapp 1032050 | 2 x 0,14 | 3.9 | 9.3 | 25 |
| UNITRONIC ROBUST C 3 x 0,14 | Lapp 1032051 | 3 x 0,14 | 4.1 | 10.8 | 28 |
| UNITRONIC ROBUST C 4 x 0,14 | Lapp 1032052 | 4 x 0,14 | 4.3 | 13.5 | 34 |
| UNITRONIC ROBUST C 5 x 0,14 | Lapp 1032053 | 5 x 0,14 | 4.6 | 15.0 | 38 |
| UNITRONIC ROBUST C 7 x 0,14 | Lapp 1032055 | 7 x 0,14 | 4.9 | 19.0 | 46 |
| UNITRONIC ROBUST C 8 x 0,14 | Lapp 1032056 | 8 x 0,14 | 5.8 | 22.0 | 60 |
| UNITRONIC ROBUST C 10 x 0,14 | Lapp 1032057 | 10 x 0,14 | 6.1 | 25.8 | 63 |
| UNITRONIC ROBUST C 12 x 0,14 | Lapp 1032058 | 12 x 0,14 | 6.3 | 28.9 | 70 |
| UNITRONIC ROBUST C 25 x 0,14 | Lapp 1032061 | 25 x 0,14 | 8.4 | 56.1 | 128 |
| UNITRONIC ROBUST C 2 x 0,25 | Lapp 1032062 | 2 x 0,25 | 4.5 | 12.7 | 33 |
| UNITRONIC ROBUST C 3 x 0,25 | Lapp 1032063 | 3 x 0,25 | 4.7 | 16.3 | 40 |
| UNITRONIC ROBUST C 4 x 0,25 | Lapp 1032064 | 4 x 0,25 | 5.0 | 18.8 | 46 |
| UNITRONIC ROBUST C 5 x 0,25 | Lapp 1032065 | 5 x 0,25 | 5.6 | 22.5 | 57 |
| UNITRONIC ROBUST C 7 x 0,25 | Lapp 1032067 | 7 x 0,25 | 6.0 | 28.6 | 69 |
| UNITRONIC ROBUST C 8 x 0,25 | Lapp 1032068 | 8 x 0,25 | 7.1 | 33.6 | 92 |
| UNITRONIC ROBUST C 10 x 0,25 | Lapp 1032069 | 10 x 0,25 | 7.5 | 42.8 | 101 |
| UNITRONIC ROBUST C 12 x 0,25 | Lapp 1032070 | 12 x 0,25 | 7.7 | 47.7 | 111 |
| UNITRONIC ROBUST C 25 x 0,25 | Lapp 1032073 | 25 x 0,25 | 10.6 | 86.5 | 202 |
| UNITRONIC ROBUST C 2 x 0,34 | Lapp 1032074 | 2 x 0,34 | 4.9 | 15.7 | 44 |
| UNITRONIC ROBUST C 3 x 0,34 | Lapp 1032075 | 3 x 0,34 | 5.1 | 20.4 | 54 |
| UNITRONIC ROBUST C 4 x 0,34 | Lapp 1032076 | 4 x 0,34 | 5.7 | 23.6 | 66 |
| UNITRONIC ROBUST C 5 x 0,34 | Lapp 1032077 | 5 x 0,34 | 6.2 | 28.2 | 78 |
| UNITRONIC ROBUST C 7 x 0,34 | Lapp 1032079 | 7 x 0,34 | 6.8 | 36.0 | 95 |
| UNITRONIC ROBUST C 8 x 0,34 | Lapp 1032080 | 8 x 0,34 | 7.8 | 45.3 | 127 |

UNITRONIC ROBUST C 10 x 0,25_

Lapp 1032069



| Product Name | Lapp Nr. | Number of cores and mm ² per conductor | Outer diameter (mm) | Copper index (kg/km) | Weight (kg/km) |
|------------------------------|--------------|---|---------------------|----------------------|----------------|
| UNITRONIC ROBUST C 10 x 0,34 | Lapp 1032081 | 10 x 0,34 | 8.3 | 53.9 | 137 |
| UNITRONIC ROBUST C 12 x 0,34 | Lapp 1032082 | 12 x 0,34 | 8.5 | 60.7 | 152 |
| UNITRONIC ROBUST C 16 x 0,34 | Lapp 1032084 | 16 x 0,34 | 9.4 | 77.9 | 191 |
| UNITRONIC ROBUST C 25 x 0,34 | Lapp 1032086 | 25 x 0,34 | 11.9 | 115.7 | 288 |