



**Description:** UNITRONIC ROBUST C 2 x 0,14\_

**Lapp code:** Lapp 1032050

The **Test voltage** of the cable Lapp 1032050 is At 0.14 mm<sup>2</sup>: 1200 V ? 0.25 mm<sup>2</sup>: 1500 V.

## Application range

- Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works
- Food and beverage industry, especially for production and processing equipment of milk and meat products
- For data processing, measurement and control engineering, safety related systems and as electronics cable
- For indoor and outdoor use

## Product Make-up

- Fine-wire/multi-wire (0.34 mm<sup>2</sup>) strand made of bare copper wires
- Core insulation made of special halogen-free compound
- Tinned-copper braiding
- Outer sheath made of special TPE
- Outer sheath colour: black

In our Cable list on next page you can find all interesting information acc. article Lapp 1032050 and much more.

## CABLE LIST - all informations you need you can find here

Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC® ROBUST C					
UNITRONIC ROBUST C 2 x 0,14	Lapp 1032050	2 x 0,14	3.9	9.3	25
UNITRONIC ROBUST C 3 x 0,14	Lapp 1032051	3 x 0,14	4.1	10.8	28
UNITRONIC ROBUST C 4 x 0,14	Lapp 1032052	4 x 0,14	4.3	13.5	34
UNITRONIC ROBUST C 5 x 0,14	Lapp 1032053	5 x 0,14	4.6	15.0	38
UNITRONIC ROBUST C 7 x 0,14	Lapp 1032055	7 x 0,14	4.9	19.0	46
UNITRONIC ROBUST C 8 x 0,14	Lapp 1032056	8 x 0,14	5.8	22.0	60
UNITRONIC ROBUST C 10 x 0,14	Lapp 1032057	10 x 0,14	6.1	25.8	63
UNITRONIC ROBUST C 12 x 0,14	Lapp 1032058	12 x 0,14	6.3	28.9	70
UNITRONIC ROBUST C 25 x 0,14	Lapp 1032061	25 x 0,14	8.4	56.1	128
UNITRONIC ROBUST C 2 x 0,25	Lapp 1032062	2 x 0,25	4.5	12.7	33
UNITRONIC ROBUST C 3 x 0,25	Lapp 1032063	3 x 0,25	4.7	16.3	40
UNITRONIC ROBUST C 4 x 0,25	Lapp 1032064	4 x 0,25	5.0	18.8	46
UNITRONIC ROBUST C 5 x 0,25	Lapp 1032065	5 x 0,25	5.6	22.5	57
UNITRONIC ROBUST C 7 x 0,25	Lapp 1032067	7 x 0,25	6.0	28.6	69
UNITRONIC ROBUST C 8 x 0,25	Lapp 1032068	8 x 0,25	7.1	33.6	92
UNITRONIC ROBUST C 10 x 0,25	Lapp 1032069	10 x 0,25	7.5	42.8	101
UNITRONIC ROBUST C 12 x 0,25	Lapp 1032070	12 x 0,25	7.7	47.7	111
UNITRONIC ROBUST C 25 x 0,25	Lapp 1032073	25 x 0,25	10.6	86.5	202
UNITRONIC ROBUST C 2 x 0,34	Lapp 1032074	2 x 0,34	4.9	15.7	44
UNITRONIC ROBUST C 3 x 0,34	Lapp 1032075	3 x 0,34	5.1	20.4	54
UNITRONIC ROBUST C 4 x 0,34	Lapp 1032076	4 x 0,34	5.7	23.6	66
UNITRONIC ROBUST C 5 x 0,34	Lapp 1032077	5 x 0,34	6.2	28.2	78
UNITRONIC ROBUST C 7 x 0,34	Lapp 1032079	7 x 0,34	6.8	36.0	95
UNITRONIC ROBUST C 8 x 0,34	Lapp 1032080	8 x 0,34	7.8	45.3	127

**UNITRONIC ROBUST C 2 x 0,14\_**

Lapp 1032050



Product Name	Lapp Nr.	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
UNITRONIC ROBUST C 10 x 0,34	Lapp 1032081	10 x 0,34	8.3	53.9	137
UNITRONIC ROBUST C 12 x 0,34	Lapp 1032082	12 x 0,34	8.5	60.7	152
UNITRONIC ROBUST C 16 x 0,34	Lapp 1032084	16 x 0,34	9.4	77.9	191
UNITRONIC ROBUST C 25 x 0,34	Lapp 1032086	25 x 0,34	11.9	115.7	288